

		2		1	
REV	E.C.N NO.	CONTENT	CHK	DATE	

NOTES:

UL Standard

- | | | | |
|---------------|------|---|------|
| Use group | B | C | D |
| Rated Current | 20A | — | 10A |
| Rated Voltage | 300V | — | 300V |

2. Wire range: 30~12AWG

IEC Standard

Pollution Degree	2
Overvoltage Category	II
Rate Impulse Voltage(KV)	4KV
Rate Voltage(V)	250
Rate Current(A)	24A

2. Torque value: M2.5, 0.4Nm
3. wire range: 0.5-2.5mm²

NOTES:

- 1.Housing: PA66(UL94V-0)
- 2.Block: Steel(Zn Plated)
- 3.Cage: Steel(M2.5/Zn Plated)
- 4.Screw: Steel(M2.5/Zn Plated)
- 5.Cover: PA66(UL94V-0)
- 6.Pin header: Copper(Sn Plated)

NOTES

- 1.Pitch: 10.0mm Poles: 02-24P
2.Operating temperature: -40°C~+105°C
3.RoHS Compliance

How to order

UL0-TB81 - 105V/10.0 - XXP - Y 0 0 0 A

Certificate Series NO.	Factory Code	Customer requirements
---------------------------	-----------------	--------------------------

- color:
- | | |
|----------|---------------|
| 1:Grey | 6:Red |
| 2:Blue | 7:transparent |
| 3:Black | 8:Yellow |
| 4:Green | 9:White |
| 5:Orange | |

Total Pitch Tolerances	Nominal dimension range	—	//
A			

[illegible]

ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTE
DWG.	LZW	DATE 22.03.03	UNITS	MM	SHEET/OF 1/1
CHK.	DATE		SCALE	1 : 1	A4
APP.	DATE				



NINGBO ULO ELECTRONICS CO.,LTD.
宁波欧路电子有限公司

DWGNO.	U10TB81Y000A
--------	--------------