





REV	E.C.N NO.	CONTENT	CHK	DATE
Type			Thread size (M/PG)	
UL0-HC06-H10B-SF-4B-M25			M25	
UL0-HC06-H10B-SF-4B-2M25			2M25	
UL0-HC06-H10B-SF-4B-M32			M32	
UL0-HC06-H10B-SF-4B-2M32			2M32	
UL0-HC06-H10B-SF-4B-PG21			PG21	
UL0-HC06-H10B-SF-4B-2PG21			2PG21	
UL0-HC06-H10B-SF-4B-PG29			PG29	
UL0-HC06-H10B-SF-4B-2PG29			2PG29	

Technical specification:

1. Material: Aluminium die-cast
2. Surface: powder-coated
3. Colour: (grey)
4. Temperature range: -40°C - +125°C
5. Degree of Protection: IP65
(acc. to IEC 60529 for coupled connector)
6. Cable entry: side entry
7. Thread size: M/PG
8. Hoods/Housings sealing: NBR



ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL		NOTE	
DWG.	SWL	DATE	2023.12.21	UNITS	MM	SHEET/OF	1/1
CHK.	DATE			SCALE	1:1	A4	
APP.	DATE			UL0-HC06-H10B-SF-4B-XX			
NAME							
NINGBO UL0 ELECTRONICS CO.,LTD.							
宁波欧路电子有限公司							
				DWGNO.			