






REV	E.C.N NO.	CONTENT	CHK	DATE
Type			Thread size (M/PG)	
ULO-HC06-H10B-SF-1L-CV-M20			M20	
ULO-HC06-H10B-SF-1L-CV-2M20			2M20	
ULO-HC06-H10B-SF-1L-CV-M25			M25	
ULO-HC06-H10B-SF-1L-CV-2M25			2M25	
ULO-HC06-H10B-SF-1L-CV-PG16			PG16	
ULO-HC06-H10B-SF-1L-CV-2PG16			2PG16	

Technical specification:

1. Material: Aluminium die-cast
2. Materia, cover1: PC
3. Surface: powder-coated
4. Colour: (grey)
5. Temperature range: -40℃ - +125℃
6. Degree of Protection: IP65
(acc. to IEC 60529 for coupled connector)
7. Locking element:
locking type: single locking latch
- material: metal
- galvanized/nickel plating
8. Cable entry: side entry
9. Thread size: M/PG
- 10 Hoods/Housings sealing: NBR

ITEM	NAME OF PART		NO. OF PART		Q-TY	MATERIAL		NOTE	
DWG.	SWL	DATE	2023.12.9		UNITS	MM	SHEET/OF	1/1	
CHK		DATE			SCALE	1:1	A4		
APP.		DATE			NAME	ULO-HC06-H10B-SF-1L-CV-XX			
 NINGBO ULO ELECTRONICS CO.,LTD. 宁波欧路电子有限公司									
					DWGNO.				