

UL Standard

Use group	B	C	D
Rated Current	8A	—	8A
Rated Voltage	300V	—	300V

3.Wire range:28-16AWG

IEC Standard

Pollution Degree	2
Overvoltage Category	II
Rate Impulse Voltage(KV)	2.5KV
Rate Voltage(V)	250V
Rate Current(A)	7A

2.Torque value:M2,0.2Nm

3. Wire range: 0.5-1.5mm²

NOTES2:

1.Housing: PA66(UL94 V-0)

2.Cover:PA66(UL94V-0)

3.Cage:Brass(Ni Plated)

4.Clamp:Phosphor Brons(Ni Plated)

5.Screw:Steel(Zn Plated/M2.0)

6.Screw:Steel(Zn Plated/M2.5)

NOTES3:

1.Pitch: 3.81mm Poles: 02-24P

2.Stripping length: 7mm

3. Operating temperature: $-40^{\circ}\text{C} \sim +105^{\circ}\text{C}$

4. RoHS Compliance

How to order

ULO-TB13 - 15KM/3.81 - XXP - Y 0 0 0 A

Certificate Series NO.	Factory Code	poles	Customer requirements
---------------------------	-----------------	-------	--------------------------

color:

1:Grey 2:Blue 3:Black

4:Green 5:Orange 6:Red

7:transparent 8:Yellow 9:White

ITEM	NAME OF PART		NO. OF PART	Q"TY	MATERIAL		NOTE	
DWG.	LZW	DATE	21.04.28	UNITS	MM	SHEET/OF		1/1
CHK.		DATE		SCALE	1:1	A4		
APP.		DATE		NAME	ULO-TB13-15KM/3.81-XXP-Y000A			
 NINGBO ULO ELECTRONICS CO.,LTD. 宁波欧路电子有限公司					DWGNO.	UL0TB13Y000A		