

NOTES1:
UL Standard

1.

Use group	B	C	D
Rated Current	BA	-	BA
Rated voltage	500V	=	500V

2.Wire range: 26~16AWG

IEC Standard

1.

Pollution Degree	2	2	2
Overvoltage Category	I	I	I
Rate Impulse Voltage(KV)	2.5KV	2.5KV	2.5KV
Rate Voltage(V)	250V	250V	250V
Rate Current(A)	BA	BA	BA

2. wire range: 0.2-1.0mm²

NOTES2:

- 1.Housing: PA66(UL94V-0)
- 2.Cover: PA66(UL94V-0)
- 3.Clamp: Phosphor Brons(Sn Plated)
- 4.Spring: Stainless Steel
- 5.Button: POM
- 6.Lever:PA66(UL94V-0)

NOTES3:

- 1.Pitch: 3.81mm Poles: 02-24P
- 2.Stripping length: 10mm
- 3.Operating temperature: -40℃~+105℃
- 4.RoHS Compliance

How to order

UL0-TB13 - 15KNG/3.81 - XXP - Y 0.0 0A



Certificate Factory poles Customer
Series NO. Code requirements

color:

- 1:Grey 2:Blue 3:Black
- 4:Green 5:Orange 6:Red
- 7:transparent 8:Yellow 9:White

Total Pitch Tolerances	Nominal dimension range													
in mm	in mm													

over	over	over	over	over	over	over	over	over	over	over	over	over	over	over
0	30	53	70	90	115	150	200	250	0	30	53	70	90	115
to	to	to	to	to	to	to	to	to	to	to	to	to	to	to
30	53	70	90	115	150	200	250	320	30	53	70	90	115	150
+0.18	+0.20	+0.25	+0.3	+0.35	+0.44	+0.55	+0.70	+0.75	+0.20	+0.25	+0.30	+0.35	+0.44	+0.55
6	5												4	0.5



ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTE
DWG.	ZJL	DATE	20.12.04	UNITS	MM
CHK.	DATE	SCALE	1 : 1	A4	1/1
APP.	DATE	NAME	UL0-TB13-15KNG/3.81-XXP-Y000A		
NINGBO UL0 ELECTRONICS CO.,LTD.			DWGNO.	UL0TB13Y000A	