

2		1		
REV	E.C.N NO.	CONTENT	CHK	DATE

NOTES1:

UL Standard

1. Rating voltage/current: 300V/8A
2. withstanding voltage: AC1600V/1Min
3. Wire range: 16~24AWG

IEC Standard

1. Pollution Degree	2	2	3
Overvoltage Category	II	III	III
Rate Impulse Voltage(KV)	2.5KV	2.5KV	2.5KV
Rate Voltage(V)	320V	160V	160V
Rate Current(A)	8A	8A	8A

2. wire range: $0.2 \sim 1.0 \text{ mm}^2$, 1.5 mm^2 sol

NOTES2:

- 1.Housing: PA66 (UL94V-0)
2.Cover: PA66 (UL94V-0)
3.Button: POM
4.Conductor: Phosphor Brons (Sn Plated)
5.Spring: Stainless Steel

NOTES3:

- 1.Pitch: 3.50mm Poles: 2x(02-24)P
2.Stripping length: 8-9mm
3.Operating temperature: -40℃~+105℃
4.RoHS Compliance

How to order

ULO-TB01 - 15KNM-B/3.5 - 2xXXP - Y 0 0 0A

Certificate
Series NO

Factory
Code

poles

Customer requirements

color:

- | | |
|---------|---------------|
| 1:Grey | 5:Orange |
| 2:Blue | 6:Red |
| 3:Black | 7:transparent |
| 4:Green | 8:Yellow |
| 9:White | |

DWG.	CKK	DATE	20.12.10	UNITS	MM	SHEET/OF	1/1
CHK.		DATE		SCALE	1:1	A4	
APP.		DATE		NAME	ULO-TB01-15KNM-B/3.5-2*XXP-Y000A		
 NINGBO ULO ELECTRONICS CO.,LTD. 宁波欧路电子有限公司				DWGNO.	ULOTB01Y000A		