

		2		1	
REV	E.C.N NO.	CONTENT	CHK	DATE	

NOTES:

UL Standard

↓

Use group	B	C	D
Rated Current	8A	—	8A
Rated Voltage	300V	—	300V

2. Wire range: 26~16AWG

IEC Standard

→

Pollution Degree	2	2	2
Overvoltage Category	II	II	II
Rate Impulse Voltage(kV)	2.5kV	2.5kV	2.5kV
Rate Voltage(V)	250V	250V	250V
Rate Current(A)	8A	8A	8A

2.wire range: 0.2-1.0mm²

NOTES:

1.Housing: PA66(UL94V-0)

2.Cover: PA66(UL94V-0

3.Clamp: Phosphor Brons(Sn Plated

4.Spring: Stainless Steel

5.Button: POM

NOTES:

1. Pitch: 3.50mm Poles: 02-24

2. Stripping length: 10mm

3. Operating temperature: $-40^{\circ}\text{C} \sim +105^{\circ}\text{C}$

4. RoHS Compliance

How to order

UL0-TB01	-	15kN/3.5	-	XXP	-	Y	0 0 0A
----------	---	----------	---	-----	---	---	--------

Certificate Series NO.	Factory Code	poles	Customer requirements
---------------------------	-----------------	-------	--------------------------

colo

1:Grey 2:Blue 3:Black

4:Green 5:Orange 6:Red

7:transparent 8:Yellow 9:White

ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL		NOTE
DWG.	Z JL	DATE	20.12.04	UNITS	MM	SHEET/OF 1/1
G/K		DATE		SCALE	1 : 1	A4
APP.		DATE				
				NAME	UL-0-TB01-15KN/3.5-XXX-Y-000A	
				DWGNO	UL01B01000A	

