



REV	E.C.N NO.	CONTENT	CHK	DATE
Type			Thread size (M/PG)	
UL0-HC07-H16B-CCTH-2L-M25			M25	
UL0-HC07-H16B-CCTH-2L-M32			M32	
UL0-HC07-H16B-CCTH-2L-M40			M40	
UL0-HC07-H16B-CCTH-2L-PG21			PG21	
UL0-HC07-H16B-CCTH-2L-PG29			PG29	



Technical specification:

1. Material: Aluminium die-cast
2. Surface: powder-coated
3. Colour: (grey)
4. Temperature range: -40℃ -- +125℃
5. Degree of Protection: IP65
(acc. to IEC 60529 for coupled connector)
6. Locking element:
locking type: double locking latch
material: stainless steel
7. Cable entry: top entry
8. Thread size: M/PG
9. Hoods/Housings sealing: NBR



ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTE
DWG.	SWL	DATE	2023.12.9	UNITS	MM
CHK.	DATE	SCALE	1:1	A4	1/1
APP.	DATE	NAME	UL0-HC07-H16B-CCTH-2L-XX		
NINGBO UL0 ELECTRONICS CO.,LTD.				DWGNO.	



宁波欧路电子有限公司