

FILE: 2021-D01VUL0

REV	EC.N NO.	CONTENT	CHK	DATE

NOTES:

UL Standard

1.

Use group	B	C	D
Rated Current	5A	5A	5A
Rated Voltage	300V/150V/300V		

3. Wire range: 20~18AWG

IEC Standard

1.

Pollution Degree	3	2	2
Overvoltage Category	III	III	I
Rate Impulse Voltage(kV)	8.0kV/ 8.0kV/ 8.0kV	400V/ 1000V/ 1000V	
Rate Voltage(V)	17.5A/ 17.5A/ 17.5A		

2. wire range: 0.2-2.5mm²

NOTES2:

- Housing: PA66(UL94V-0)
- Cover: PA66(UL94V-0)
- Lever: PA66(UL94V-0)
- Spring: Stainless
- Pin header: Copper alloy(Sn Plated)
- Calboard:PA66(UL94V-0)

NOTES3:

- Pitch: 7.5mm Poles: 02-24P
- Stripping length: 10mm
- Operating temperature: -40℃~+105℃
- RoHS Compliance

How to order

ULO-TB12 - 235/75 - XXP - Y 000 A

Certificate Factory poles
Series NO. Code Customer requirements

color:

- 1:Grey 6:Red
- 2:Blue 7:transparent
- 3:Black 8:Yellow
- 4:Green 9:White
- 5:Orange

PCB LAYOUT

Total Pitch Tolerances

Nominal dimension range

1

=

—

//

ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTE
DWG	LZW	DATE	21.05.10	UNITS	MM
CHK	DATE	SCALE	1:1	A4	1/1
APP	DATE	NAME	ULO-TB12-235/75-XXP-Y000A		



NINGBO ULO ELECTRONICS CO.,LTD.

UL0TB12Y000A