





REV	E.C.N NO.	CONTENT	CHK	DATE
Type			Thread size (M/Pg)	
UL0-HC08-H24B-CCT-2L-M25			M25	
UL0-HC08-H24B-CCT-2L-M32			M32	
UL0-HC08-H24B-CCT-2L-PG21			PG21	
UL0-HC08-H24B-CCT-2L-PG29			PG29	

Technical specification:

1. Material: Aluminium die-cast
2. Surface: powder-coated
3. Colour: (grey)
4. Temperature range: -40℃ - +125℃
5. Degree of Protection: IP65
(acc. to IEC 60529 for coupled connector)
6. 0 Locking element:
locking type: double locking latch
material: stainless steel
7. Cable entry: top entry
8. Thread size: M/Pg
9. Hoods/Housings sealing: NBR



ITEM	NAME OF PART		NO. OF PART		Q-TY	MATERIAL		NOTE	
DWG.	SWL	DATE	2023.12.9		UNITS	MM	SHEET/OF	1/1	
CHK		DATE			SCALE	1:1	A4		
APP.		DATE			NAME	UL0-HC08-H24B-CCT-2L-XX			
 NINGBO UL0 ELECTRONICS CO.,LTD. 宁波欧路电子有限公司					DWGNO.				