



Pollution Degree	2
Overvoltage Category	III
Rate Impulse Voltage(KV)	4.0KV
Rate Voltage(V)	320V
Rate Current(A)	20A

1

IEC Standard

1

NOTES:

1.Housing: PA66(UL94V-0)

2.Solder Pin: Red copper(Sn Plated)

NOTES:

1.Pitch: 5.08mm Poles: 02~24P

2. Operating temperature: $-40^{\circ}\text{C} \sim +105^{\circ}\text{C}$

4. RoHS Compliance

How to order

UL0-TB27 - 2VC/5.08 - XXP - Y 0 0 0 A

Certificate Series NO.	Factory Code	poles	Customer requirements
---------------------------	-----------------	-------	--------------------------

color: _____

1:Grey 6:Red
2:Blue 7:transparent
3:Black 8:Yellow
4:Green 9:White
5:Orange

ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL		NOTE
DWG.	Z.JL	DATE 20.11.28	UNITS	MM	SHEET/OF	1/1
CHK.		DATE	SCALE	1 : 1	A4	
APP.		DATE				
NINGBO ULIO ELECTRONICS CO.,LTD.			ULIO-1B21-2V(C5.08-XXP-4.000A			
宁波欧路电子有限公司			ULIOB27Y000A			
						