



REV	E.C.N NO.	CONTENT	CHK	DATE
		Type	Thread size (M/PG)	
		ULO-HC10-H48B-SF-1L-MCV-M32	M32	
		ULO-HC10-H48B-SF-1L-MCV-2M32	2M32	
		ULO-HC10-H48B-SF-1L-MCV-M40	M40	
		ULO-HC10-H48B-SF-1L-MCV-2M40	2M40	
		ULO-HC10-H48B-SF-1L-MCV-PG29	PG29	
		ULO-HC10-H48B-SF-1L-MCV-2PG29	2PG29	
		ULO-HC10-H48B-SF-1L-MCV-PG36	PG36	
		ULO-HC10-H48B-SF-1L-MCV-2PG36	2PG36	



Technical specification:

1. Material: Aluminium die-cast
2. Materia, coverl: Aluminium die-cast
3. Surface: powder-coated
4. Colour: (grey)
5. Temperature range: -40℃ - +125℃
6. Degree of Protection: IP65
(acc. to IEC 60529 for coupled connector)
7. Locking element:
locking type:single locking latch
material: stainless steel
8. Cable entry: side entry
9. Thread size: M/PG
10. Hoods/Housings sealing: NBR



ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTE
DWG.	SWL	DATE	2023.12.9	UNITS	MM
CHK.	DATE			SCALE	1:1
APP.	DATE				A4
				NAME	ULO-HC10-H48B-SF-1L-MCV-XX
				DWGNO.	