



Type	Thread size (M/PG)
ULO-HC10-H48B-SF-1L-CV-M32	M32
ULO-HC10-H48B-SF-1L-CV-2M32	2M32
ULO-HC10-H48B-SF-1L-CV-M40	M40
ULO-HC10-H48B-SF-1L-CV-2M40	2M40
ULO-HC10-H48B-SF-1L-CV-PG29	PG29
ULO-HC10-H48B-SF-1L-CV-2PG29	2PG29
ULO-HC10-H48B-SF-1L-CV-PG36	PG36
ULO-HC10-H48B-SF-1L-CV-2PG36	2PG36

Technical specification:

1. Material: Aluminium die-cast
2. Materia, coverl: PC
3. Surface: powder-coated
4. Colour: (grey)
5. Temperature range: -40℃ - +125℃
6. Degree of Protection: IP65
(acc. to IEC 60529 for coupled connector)
7. Locking element:
locking type:single locking latch
material: stainless steel
8. Cable entry: side entry
9. Thread size: M/PG
10. Hoods/Housings sealing: NBR



ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTE
DWG.	SWL	DATE	2023.12.9	UNITS	MM
CHK.	DATE	SCALE	1:1	A4	1/1
APP.	DATE	NAME	ULO-HC10-H48B-SF-1L-CV-XX		
NINGBO ULO ELECTRONICS CO.,LTD.			DWGNO.		
宁波欧路电子有限公司					