

NOTES:

UL Standard

1.

2. Wire range: 22~14AWG

IEC Standard

1.

NOTES:

1.Housing: PA66(UL94V-0)

2.5Screw: Steel(M3/Ni Plated)

3.Pin header: Copper alloy(M3/Sn Plated)

4. Cover: PC(UL94V-2)

NOTES3

1.Pitch: 9.5mm Poles: 02-22P

2.Stripping length: 9mm

3. Operating temperature: $-40^{\circ}\text{C} \sim +105^{\circ}\text{C}$

4. RoHS Compliance

How to order

UL0-TB42	-	48C/A	-	XXP	-	Y	100A
----------	---	-------	---	-----	---	---	------

Certificate Factory poles

Series NO.	Code
------------	------

Customer requirements

_____color:

1:Grey 6:Red

2:Blue 7:transparent

3:Black 8:Yellow

4:Green 9:White

5:0range

± 0.18	± 0.20	± 0.25	± 0.3	± 0.35	± 0.44	± 0.55	± 0.70	± 0.75	± 0.20	± 0.25	± 0.30	± 0.35	± 0.44	± 0.55	± 0.70	± 0.80	± 0.90	0.2	0.3	0.3	0.2	0.3	0.5
------------	------------	------------	-----------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	------------	-----	-----	-----	-----	-----	-----

ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTE
DWG.	LZW	DATE 21.05.31	UNITS	MM	SHEET/OF 1/1
G/K	DATE		SCALE 1 : 1	A4	
APP.	DATE		NAME	ULO-1B42-48C/A-XP-Y100A	
 NINGBO ULO ELECTRONICS CO.,LTD. 宁波欧路电子有限公司			DWGNO.	ULO1B42Y100A	

