





REV	E.C.N NO.	CONTENT	CHK	DATE
		Type	Thread size (M/PG)	
		UL0-HC05-H6B-SFH-1L-M25	M25	
		UL0-HC06-H6B-SFH-1L-2M25	2M25	
		UL0-HC06-H6B-SFH-1L-M32	M32	
		UL0-HC06-H6B-SFH-1L-2M32	2M32	
		UL0-HC06-H6B-SFH-1L-PC21	PC21	
		UL0-HC06-H6B-SFH-1L-2PC21	2PC21	
		UL0-HC06-H6B-SFH-1L-PC29	2PC29	
		UL0-HC06-H6B-SFH-1L-2PC29	2PC29	

Technical specification:

1. Material: Aluminium die-cast
2. Surface: powder-coated
3. Colour: (grey)
4. Temperature range: -40℃ - +125℃
5. Degree of Protection: IP65
(acc. to IEC 60529 for coupled connector)
6. Locking element:
locking type: single locking latch
material: metal galvanized/nickel plating
7. Cable entry: side entry
8. Hoods/Housings sealing: NBR



ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTE	
DWG.	SWL	DATE	2023.12.19	UNITS	MM	SHEET/OF 1/1
CHK.	DATE	DATE		SCALE	1:1	A4
APP.	DATE					
				NAME	UL0-HC05-H6B-SFH-1L-XX	
				DWGNO.		

NINGBO UL0 ELECTRONICS CO., LTD.
宁波欧路电子有限公司