



特点 Featurest

- 采用不同连接技术的接线端子可随意组合, 灵活性高
- 采用桥接并结构, 桥接和测试更轻松
- 额外集成测试孔, 无需移除导线或桥接件
- 采用统一的桥接、表示和测试配件, 节约更多成本
- 丰富的数字数据

- Terminal blocks with different connection technologies can be combined at will for greater flexibility
- Bridge and test is easier with bridge well structure
- Additional integrated test holes without removing wires or bridges
- Additional cost savings with unified bridging, marking and test accessories
- Rich numbers




说明 Specification / 简图 Schematic Drawing

直插式接线端子: 可安装在NS35 型导轨上
Push-in terminal block
Can be installed on tracks NS35 type

CPT-1.5PE 直插式接线端子 Push-in terminal block		
厚/宽/高	3.5/45/30.5/32	
Thickness/Width/Height	3.5/45/30.5/32	
刚性导线 (mm ²)	柔性导线 (mm ²)	
Rigid cable	Soft cable	
AWG:26-14	0.2-1.5	0.2-1.5
型号 Model	颜色 Color	

CPT-1.5/2PE 直插式接线端子 Push-in terminal block		
厚/宽/高	3.5/65.4/41.1/42.6	
Thickness/Width/Height	3.5/65.4/41.1/42.6	
刚性导线 (mm ²)	柔性导线 (mm ²)	
Rigid cable	Soft cable	
AWG:26-14	0.2-1.5	0.2-1.5
型号 Model	颜色 Color	


(1) 端板 End plate



D-CPT-1.5

D-CPT-1.5/2

(2) 插拔式桥接件: 用于端子中央实现横向桥接齿背绝缘处可标识可分: 2-位、3-位、10-位
Insert-pull type bridging component: used to realize crosswise bridging at center of terminal, the mark of rail insulation can be divided into: 2-bit, 3-bit, 10-bit.



CFBS2-3.5
CFBS3-3.5
CFBS10-3.5

CFBS2-3.5
CFBS3-3.5
CFBS10-3.5

(3) 螺丝刀 Screwdriver



0.4×2.5

0.4×2.5

(4) 扁平标记条: 共10条, 每条10位
可嵌入端子外侧标识槽进行标示。
Flat mark strip: 10 strips totally, 10 bits per strip, it could be plugged in mark groove of terminal outer side for marking.



(5) 标记条: 有横向和竖向两种字体, 10位。
Mark bar: two character styles, with horizontal and vertical arrangements, ten spaced.



ZB3




ZB3

(6) 终端固定件: 对端子排终端其固定件作用。标记夹和标记条可卡在它上进行标识。
Terminal fixed component: Imposing fixed function on terminal rows' termination the mark clamp and mark strip can be blocked onto it for marking



E/UK3

E/UK3



CPT-1.5/1-2PE 直插式接线端子 Push-in terminal block		
厚/宽/高	3.5/54.1/30.5/32	
Thickness/Width/Height	Height	
刚性导线	柔性导线	
(mm ²)	(mm ²)	
Rigid cable	Soft cable	
AWG:26-14	0.2-1.5	0.2-1.5
型号 Model	颜色 Color	

CPT-1.5/1-2PE 黄 + 绿 (PE)

D-CPT-1.5/1-2

CFBS2-3.5
CFBS3-3.5
CFBS10-3.5

0.4×2.5

ZB3

E/UK3

CPT-1.5/2-2PE 直插式接线端子 Push-in terminal block		
厚/宽/高	3.5/63.2/30.5/32	
Thickness/Width/Height	Height	
刚性导线	柔性导线	
(mm ²)	(mm ²)	
Rigid cable	Soft cable	
AWG:26-14	0.2-1.5	0.2-1.5
型号 Model	颜色 Color	

CPT-1.5/2-2PE 黄 + 绿 (PE)

D-CPT-1.5/2-2

CFBS2-3.5
CFBS3-3.5
CFBS10-3.5

0.4×2.5

ZB3

E/UK3

CPT-2.5PE 直插式接线端子 Push-in terminal block		
厚/宽/高	5.2/48.6/35.5/36.8	
Thickness/Width/Height	Height	
刚性导线	柔性导线	
(mm ²)	(mm ²)	
Rigid cable	Soft cable	
AWG:26-12	0.2-4	0.2-4
型号 Model	颜色 Color	

CPT-2.5PE 黄 + 绿 (PE)

D-CPT-2.5

CFBS2-5
CFBS3-5
CFBS10-5

0.6×3.5


ZBFM5

ZB5

E/UK3

特点 Featurest

- 采用不同连接技术的接线端子可随意组合, 灵活性高
- 采用桥接并结构, 桥接和测试更轻松
- 额外集成测试孔, 无需移除导线或桥接件
- 采用统一的桥接、表示和测试配件, 节约更多成本
- 丰富的数字数据
- Terminal blocks with different connection technologies can be combined at will for greater flexibility
- Bridge and test is easier with bridge well structure
- Additional integrated test holes without removing wires or bridges
- Additional cost savings with unified bridging, marking and test accessories
- Rich numbers



CPT-2.5/2PE 直插式接地端子 Push-in ground terminal block		
厚/宽/高	5.2/68.4/46.1/47.6	
Thickness/Width/Height	5.2/68.4/46.1/47.6	
刚性导线 (mm²)	柔性导线 (mm²)	
Rigid cable	Soft cable	
AWG:26-12	0.2-4	0.2-4

CPT-2.5/1-2PE 直插式接地端子 Push-in ground terminal block		
厚/宽/高	5.2/60.4/35.5/36.8	
Thickness/Width/Height	5.2/60.4/35.5/36.8	
刚性导线 (mm²)	柔性导线 (mm²)	
Rigid cable	Soft cable	
AWG:26-12	0.2-4	0.2-4

说明 Specification / 简图 Schematic Drawing

直插式接线端子: 可安装在NS35 型导轨上
Push-in terminal block
Can be installed on tracks NS35 type

型号 Model

颜色 Color

CPT-2.5/2PE

黄 + 绿 (PE)


型号 Model

颜色 Color

CPT-2.5/1-2PE

黄 + 绿 (PE)


(1) 端板 End plate



D-CPT-2.5/2

D-CPT-2.5/1-2

(2) 插拔式桥接件: 用于端子中央实现横向桥接齿背绝缘处可标识可分: 2-位、3-位、10-位
Insert-pull type bridging component: used to realize crosswise bridging at center of terminal, the mark of rail insulation can be divided into: 2-bit, 3-bit, 10-bit.



CFBS2-5
CFBS3-5
CFBS10-5

CFBS2-5
CFBS3-5
CFBS10-5

(3) 螺丝刀 Screwdriver



0.6x3.5

0.6x3.5

(4) 扁平标记条: 共10条, 每条10位
可插入端子外侧标识槽进行标识。
Flat mark strip: 10 strips totally, 10 bits per strip, it could be plugged in mark groove of terminal outer side for marking.



ZBFM5

ZBFM5

(5) 标记条: 有横向和竖向两种字体, 10位。
Mark bar: two character styles, with horizontal and vertical arrangements, ten spaced.



ZB5




ZB5

(6) 终端固定件: 对端子排终端其固定件作用。标记夹和标记条可卡在它上进行标识。
Terminal fixed component: Imposing fixed function on terminal rows' termination the mark clamp and mark strip can be blocked onto it for marking



E/UK3

E/UK3



CPT-2.5/2-2PE		
直插式接地端子 Push-in ground terminal block		
厚/宽/高	5.2/72.4/35.5/36.8	
Thickness/Width/Height		
刚性导线	柔性导线	
(mm ²)	(mm ²)	
Rigid cable	Soft cable	
AWG:26-12	0.2-4	0.2-4

CPT-4PE		
直插式接地端子 Push-in ground terminal block		
厚/宽/高	6.2/55.8/35.5/36.8	
Thickness/Width/Height		
刚性导线	柔性导线	
(mm ²)	(mm ²)	
Rigid cable	Soft cable	
AWG:24-10	0.2-6	0.2-6

取决于6mm² 刚性导线的最大负载电流
Depends on the maximum load current of 6mm² rigid wire

CPT-4/2PE		
直插式接地端子 Push-in ground terminal block		
厚/宽/高	6.2/83.7/45.9/47.4	
Thickness/Width/Height		
刚性导线	柔性导线	
(mm ²)	(mm ²)	
Rigid cable	Soft cable	
AWG:24-10	0.2-6	0.2-6



型号 Model	颜色 Color
CPT-2.5/2-2PE	黄 + 绿 (PE)
D-CPT-2.5/2-2	
CFBS2-5 CFBS3-5 CFBS10-5	
0.6×3.5	
ZBFM5	
ZB5	
E/UK3	

型号 Model	颜色 Color
CPT-4PE	黄 + 绿 (PE)
D-CPT-4	
CFBS2-6 CFBS3-6 CFBS10-6	
0.6×3.5	
ZBFM6	
ZB6	
E/UK3	

型号 Model	颜色 Color
CPT-4/2PE	黄 + 绿 (PE)
D-CPT-4/2	
CFBS2-6 CFBS3-6 CFBS10-6	
0.6×3.5	
ZBFM6	
ZB6	
E/UK3	

特点 Featurest

- 采用不同连接技术的接线端子可随意组合, 灵活性高
- 采用桥接并结构, 桥接和测试更轻松
- 额外集成测试孔, 无需移除导线或桥接件
- 采用统一的桥接、表示和测试配件, 节约更多成本
- 丰富的数字数据
- Terminal blocks with different connection technologies can be combined at will for greater flexibility
- Bridge and test is easier with bridge well structure
- Additional integrated test holes without removing wires or bridges
- Additional cost savings with unified bridging, marking and test accessories
- Rich numbers



说明 Specification / 简图 Schematic Drawing

直插式接线端子: 可安装在NS35 型导轨上
Push-in terminal block
Can be installed on tracks NS35 type

CPT-4PE/1-2 直插式接地端子 Push-in ground terminal block		
厚/宽/高	6.2/66.4/35.5/36.8	高
Thickness/Width/Height	6.2/66.4/35.5/36.8	Height
刚性导线 (mm ²)	柔性导线 (mm ²)	
Rigid cable	Solf cable	
AWG:24-10	0.2-6	0.2-6
型号 Model	颜色 Color	

CPT-4PE/1-2


黄 + 绿 (PE)

CPT-4PE/2-2 直插式接地端子 Push-in ground terminal block		
厚/宽/高	6.2/76.9/35.3/36.8	高
Thickness/Width/Height	6.2/76.9/35.3/36.8	Height
刚性导线 (mm ²)	柔性导线 (mm ²)	
Rigid cable	Solf cable	
AWG:24-10	0.2-6	0.2-6
型号 Model	颜色 Color	

CPT-4PE/2-2

黄 + 绿 (PE)


(1) 端板 End plate



D-CPT-4/1-2

D-CPT-4/2-2

(2) 插拔式桥接件: 用于端子中央实现横向桥接齿背绝缘处可标识可分: 2-位、3-位、10-位
Insert-pull type bridging component: used to realize crosswise bridging at center of terinal, the mark of rail insulation can be divided into:2-bit.3-bit.10-bit.



CFBS2-6
CFBS3-6
CFBS10-6

CFBS2-6
CFBS3-6
CFBS10-6

(3) 螺丝刀Screwdriver



0.6×3.5

0.6×3.5

(4) 扁平标记条: 共10条, 每条10位
可堪入端子外侧标识槽进行标示。
Flat mark strip:10 strips totally, 10 bits per strip,it could be plugged in mark groove of terminal outer side for marking.



ZBFM6

ZBFM6

(5) 标记条: 有横向和竖向两种字体, 10位。
Mark bar: two character styles, with horizontal and vertical arrangements, ten spaced.



ZB6




ZB6

(6) 终端固定件: 对端子排终端其固定件作用。标记夹和标记条可卡在它上进行标识。
Terminal fixed component:Imposing fixed functionon terminal rows' s termination the,mark clam pand mark strip can be blocked onto it for marking



E/UK3

E/UK3



CPT-6PE		
直插式接地端子 Push-in ground terminal block		
厚/宽/高	8.2/57/42.2/43.7	
Thickness/Width/Height	8.2/57/42.2/43.7	
刚性导线	柔性导线	
(mm ²)	(mm ²)	
Rigid cable	Soft cable	
AWG:20-8	0.5-10	0.5-10
型号 Model	颜色 Color	

CPT-6/1-2PE		
直插式接地端子 Push-in ground terminal block		
厚/宽/高	8.2/74.1/42.2/43.7	
Thickness/Width/Height	8.2/74.1/42.2/43.7	
刚性导线	柔性导线	
(mm ²)	(mm ²)	
Rigid cable	Soft cable	
AWG:20-8	0.5-10	0.5-10
型号 Model	颜色 Color	

CPT-6PE/2-2		
直插式接地端子 Push-in ground terminal block		
厚/宽/高	8.2/90.5/42.2/43.7	
Thickness/Width/Height	8.2/90.5/42.2/43.7	
刚性导线	柔性导线	
(mm ²)	(mm ²)	
Rigid cable	Soft cable	
AWG:20-8	0.5-10	0.5-10
型号 Model	颜色 Color	

CPT-6PE 黄 + 绿 (PE)

CPT-6/1-2PE 黄 + 绿 (PE)

CPT-6PE/2-2 黄 + 绿 (PE)

D-CPT-6

D-CPT-6/1-2

D-CPT-6/2-2

CFBS2-8
CFBS3-8
CFBS4-8
CFBS5-8
CFBS10-8

CFBS2-8
CFBS3-8
CFBS4-8
CFBS5-8
CFBS10-8

CFBS2-8
CFBS3-8
CFBS4-8
CFBS5-8
CFBS10-8

0.8×4

0.8×4

0.8×4

ZBFM8

ZBFM8

ZBFM8

ZB8

ZB8

ZB8



E/UK3

E/UK3

E/UK3

特点 Featurest

- 采用不同连接技术的接线端子可随意组合, 灵活性高
- 采用桥接并结构, 桥接和测试更轻松
- 额外集成测试孔, 无需移除导线或桥接件
- 采用统一的桥接、表示和测试配件, 节约更多成本
- 丰富的数字数据
- Terminal blocks with different connection technologies can be combined at will for greater flexibility
- Bridge and test is easier with bridge well structure
- Additional integrated test holes without removing wires or bridges
- Additional cost savings with unified bridging, marking and test accessories
- Rich numbers



说明 Specification / 简图 Schematic Drawing

直插式接线端子: 可安装在NS35 型导轨上
Push-in terminal block
Can be installed on tracks NS35 type

CPT-10PE 直插式接地端子 Push-in ground terminal block		
厚/宽/高	10.2/67.7/49.6/51.1	
Thickness/Width/Height	10.2/67.7/49.6/51.1	
刚性导线 (mm²)	柔性导线 (mm²)	
Rigid cable	Self cable	
AWG:20-6	0.5-16	0.5-16

型号 Model	颜色 Color
----------	----------

CPT-10PE

黄 + 绿 (PE)


CPT-16PE 直插式接地端子 Push-in ground terminal block		
厚/宽/高	12.2/75.4/52.6/54.1	
Thickness/Width/Height	12.2/75.4/52.6/54.1	
刚性导线 (mm²)	柔性导线 (mm²)	
Rigid cable	Self cable	
AWG:20-4	0.5-25	0.5-25

型号 Model	颜色 Color
----------	----------

CPT-16PE

黄 + 绿 (PE)


(1) 端板 End plate



D-CPT-10

D-CPT-16

(2) 插拔式桥接件: 用于端子中央实现横向桥接齿背绝缘处可标识可分: 2-位、3-位、10-位
Insert-pull type bridging component: used to realize crosswise bridging at center of terminal, the mark of rail insulation can be divided into: 2-bit, 3-bit, 10-bit.

CFBS2-10
CFBS5-10

CFBS2-12

(3) 螺丝刀 Screwdriver



0.6x3.5

1.0x5.5

(4) 扁平标记条: 共10条, 每条10位
可插入端子外侧标识槽进行标示。
Flat mark strip: 10 strips totally, 10 bits per strip, it could be plugged in mark groove of terminal outer side for marking.



(5) 标记条: 有横向和竖向两种字体, 10位。
Mark bar: two character styles, with horizontal and vertical arrangements, ten spaced.



ZB10

ZB12

(6) 终端固定件: 对端子排终端其固定件作用。标记夹和标记条可卡在它上进行标识。
Terminal fixed component: Imposing fixed function on terminal rows' termination, the mark clamp and mark strip can be blocked onto it for marking



E/UK3

E/UK3