


本系列端子默认颜色: 黄绿两色 (PE)

The default color of this series terminal: yellow and green (PE)



实用特征 Features

CUK 通用型接地端子系列产品主要用于接地功能, 或接零功能, 具有相应规格接线端子的电流承载能力。其低接触电阻, 防腐蚀连接点, 黄绿标志均能满足有关技术标准的规定。

CUK protective earth terminals are used for grounding or protective zeroing. Their load capacity corresponds to the terminal size. They have low contact resistance, corrosion-resistant contacts and yellow-green marking for protective conductor identification.

说明 Specification / 简图 Schematic Drawing

接地端子: 带黄绿色绝缘外壳, 可安装在NS32 □ 型, 或NS35 □ 型导轨上。
Landing terminal: with yellow/green insulation outer-case, it can be installed in the NS32 □ type or NS35 □ type track.

(1) 边插式联络件: 全绝缘2 位; 全绝缘3 位; 全绝缘10 位。
Side adaptor: Full insulation in 2 digit. Full insulation in 3 digit. Full insulation in 10 digit.



(2) 标记条: 有横向和竖向两种字体, 10 位。
Mark bar: two character styles, with horizontal and vertical arrangements, ten spaced.




CUK-2.5B/PE 螺钉式接线端子 Screw Type Terminal

厚/宽/高 □ 高	6.2/42.5/42/49.5	
Thickness/Width/Height/ □ Height		
刚性导线 (mm²)	柔性导线 (mm²)	
AWG:24-12	Rigid cable	Soft cable
IEC 60947-7-2	0.2-4	0.2-2.5

型号 Model 颜色 Color

CUK-2.5B/PE 黄+绿(PE)

ZB6



CUK-10PE 螺钉式接线端子 Screw Type Terminal

厚/宽/高 □ 高	10.2/42.5/47/54.5	
Thickness/Width/Height/ □ Height		
刚性导线 (mm²)	柔性导线 (mm²)	
AWG:20-6	Rigid cable	Soft cable
IEC 60947-7-2	0.5-16	0.5-10

型号 Model 颜色 Color

CUK-10PE 黄+绿(PE)

ZB10

实用特征 Features


CUK 通用型接地端子系列产品主要用于接地功能, 或接零功能, 具有相应规格接线端子的电流承载能力。其低接触电阻, 防腐蚀连接点, 黄绿标志均能满足有关技术标准的规定。

CUK protective earth terminals are used for grounding or protective zeroing. Their load capacity corresponds to the terminal size. They have low contact resistance, corrosion-resistant contacts and yellow-green marking for protective conductor identification.


说明 Specification / 简图 Schematic Drawing


接地端子: 带黄绿色绝缘外壳, 可安装在NS32 □ 型, 或NS35 □ 型导轨上。
Landing terminal: with yellow/green insulation outer-case, it can be installed in the NS32 □ type or NS35 □ type track.

(1) 边插式联络件: 全绝缘2 位; 全绝缘3 位; 全绝缘10 位。
Side adaptor: Full insulation in 2 digit. Full insulation in 3 digit. Full insulation in 10 digit.




(2) 标记条: 有横向和竖向两种字体, 10 位。
Mark bar: two character styles, with horizontal and vertical arrangements, ten spaced.





CUK-2.5PE 螺钉式接线端子 Screw Type Terminal		
厚/宽/高 Thickness/Width/Height	5.2/42.5/47/54.5	
刚性导线 (mm ²)	柔性导线 (mm ²)	
AWG:24-12	Rigid cable	Solf cable
IEC 60947-7-2	0.2-4	0.2-2.5
型号 Model	颜色 Color	

CUK-2.5PE 黄+绿(PE)



CUK-4PE 螺钉式接线端子 Screw Type Terminal		
厚/宽/高 Thickness/Width/Height	6.2/42.5/47/54.5	
刚性导线 (mm ²)	柔性导线 (mm ²)	
AWG:24-10	Rigid cable	Solf cable
IEC 60947-7-2	0.2-6	0.2-4
型号 Model	颜色 Color	

CUK-4PE 黄+绿(PE)




CUK-6PE 螺钉式接线端子 Screw Type Terminal		
厚/宽/高 Thickness/Width/Height	8.2/42.5/47/54.5	
刚性导线 (mm ²)	柔性导线 (mm ²)	
AWG:24-8	Rigid cable	Solf cable
IEC 60947-7-2	0.2-10	0.2-6
型号 Model	颜色 Color	

CUK-6PE 黄+绿(PE)

ZB5


ZB6

ZB8



CUK-16PE 螺钉式接线端子 Screw Type Terminal		
厚/宽/高 Thickness/Width/Height	12.2/42.5/54/61.5	
刚性导线 (mm ²)	柔性导线 (mm ²)	
AWG:12-4	Rigid cable	Solf cable
IEC 60947-7-2	2.5-25	4-16
型号 Model	颜色 Color	

CUK-16PE 黄+绿(PE)



CUK-35PE 螺钉式接线端子 Screw Type Terminal		
厚/宽/高 Thickness/Width/Height	15.2/56/52/59.5	
刚性导线 (mm ²)	柔性导线 (mm ²)	
AWG:14-2	Rigid cable	Solf cable
IEC 60947-7-2	2.5-35	2.5-35
型号 Model	颜色 Color	

CUK-35PE 黄+绿(PE)



CUK-50PE 螺钉式接线端子 Screw Type Terminal		
厚/宽/高 Thickness/Width/Height	20.2/70.5/83.5/91	
刚性导线 (mm ²)	柔性导线 (mm ²)	
AWG:6-0	Rigid cable	Solf cable
IEC 60947-7-2	16-50	25-50
型号 Model	颜色 Color	

CUK-50PE 黄+绿(PE)

ZB12

ZB10

ZB10