



FILE: 2020-D01\ULO


REV	E.C.N NO.	CONTENT	CHK	DATE











NOTES1:

UL Standard

1.Rating voltage/current: 600V/40A

2.withstanding voltage: AC4000V/1Min

IEC Standard

1.Torque value: M5, 2.0Nm

2. wire range: 1.5～8.0mm², 10.0mm²sol

NOTES2:

1.Housing Left: PA66 (UL94V-0)

2.Housing Centre: PA66 (UL94V-0)

3.Housing Right: PA66 (UL94V-0)

4.Screw: Steel (M5, Zn Plated)

5.Nut: Steel (Zn Plated)

6.Conductor: Brass (Ni Plated)

7.Long Screw: Steel (M3, Zn Plated)

8.Cover:PC

NOTES3:

1.Pitch: 13.00mm Poles: 02-14P

2.Operating temperature: -40℃～+105℃

3.RoHS Compliance

How to order

ULO - DSTB/8 - XXP - Y 0 0 0A

- ULO: Certificate Series NO.
- DSTB/8: Factory Code
- XXP: poles
- Y: color:
 1:Grey 5:Orange
 2:Blue 6:Red
 3:Black 7:transparent
 4:Green 8:Yellow
 9:White
- 0 0 0A: Customer requirements

Total Pitch Tolerances in mm									Nominal dimension range in mm									⊥		⫩	—	//	
over 0 to 30	over 30 to 53	over 53 to 70	over 70 to 90	over 90 to 115	over 115 to 150	over 150 to 200	over 200 to 250	over 250 to 320	over 0 to 30	over 30 to 53	over 53 to 70	over 70 to 90	over 90 to 115	over 115 to 150	over 150 to 200	over 200 to 250	over 250 to 320	over 0 to 10	over 10	all	over 0 to 100	over 100 to 150	over 150
±0.18	±0.20	±0.25	±0.3	±0.35	±0.44	±0.55	±0.70	±0.75	±0.20	±0.25	±0.30	±0.35	±0.44	±0.55	±0.70	±0.80	±0.90	0.2	0.3	0.3	0.2	0.3	0.5

ITEM	NAME OF PART		NO. OF PART	Q"TY	MATERIAL	NOTE
DWG.	CKK	DATE	21.09.22	UNITS	MM	SHEET/OF 1/1
CHK.		DATE		SCALE	1 : 1	A4
APP.		DATE		NAME	ULO-DSTB/8-XXP-Y000A	
NINGBO ULO ELECTRONICS CO.,LTD. 宁波欧路电子有限公司				DWGNO.	ULOY000A	