

Application

Suitable to charge batteries that are less than 100AH and 12V.

Model & Spec

Spec	Outline size(cm)
1201	11 × 16 × 28
1202	11 × 16 × 28
1203	11 × 16 × 28
1204	11 × 16 × 28
1205	11 × 16 × 28
1206	11 × 16 × 28
1207	11 × 16 × 28
1208	11 × 16 × 28
1210	35 × 11 × 17
1215	35 × 11 × 17
1220	35 × 11 × 17



GCA silicon rectifier charger

The charging current and voltage are regulated manually for GCA charger. It features high reliability & strong power, with silicon diode as rectifying element. It is suitable for charging of variety battery.

Application

Suitable to charge various type of batteries in various capacity.

Model & Spec

Spec	Outline size(cm)
6-12V/5A	22 × 18 × 16
6-12V/10A	25 × 23 × 20
6-12V/20A	28 × 30 × 17
6-12V/30A	28 × 30 × 17
6-24V/5A	22 × 18 × 16
6-24V/10A	25 × 23 × 20
6-24V/20A	28 × 30 × 17
6-24V/30A	28 × 30 × 17
6-36V/5A	22 × 18 × 16
6-36V/10A	25 × 23 × 20
6-36V/20A	28 × 30 × 17
6-36V/30A	36 × 38 × 22
6-36V/50A	36 × 40 × 71
6-48V/10A	28 × 30 × 17
6-48V/20A	28 × 30 × 17
6-48V/30A	36 × 38 × 22
6-48V/50A	36 × 40 × 71
6-48V/80A	61 × 60 × 79
6-48V/100A	61 × 45 × 79
6-72V/10A	28 × 30 × 17
6-72V/20A	36 × 38 × 22
6-72V/30A	36 × 45 × 69
6-72V/50A	36 × 40 × 71
6-72V/80A	61 × 60 × 79
6-72V/100A	61 × 60 × 79

Other specifications can be customized at user's requirement.



KCA fast charger

KCA fast charger adopts advanced high frequency switching power supply technology, divides the charging procedure into three stages, I . e. constant current, constant voltage and floating charge, it can charge quickly with high efficiency. With small volume, light weight, full- automatic control and simple operating mode, it is very suitable for minitype motors or low charging power batteries of various voltage.