

Double delay relay GRT6-2T Instruction Manual



General

■Applications

-For gradual switching of heavy powers (e.g. el.heating), prevents current strokes in the main.

■Function Features

- 2x Delay ON (2 time relays in one)

-Time scale 0.1s - 10 days divided into 10 time ranges:

0.1s - 1s / 1s - 10s / 0.1min - 1min / 1min - 10min / 0.1h - 1h / 1h - 10hrs
/ 0.1 day - 1 day / 1 day - 10 days / ON / OFF.

-Times t1 and t2 are independantly adjustable.

- t1 and t2 are switched on after supply voltage connection

- Relay status is indicated by LED.

- 1-MODULE,DIN rail mounting.


■Model and connotation




Technical parameters

Technical parameters	GRT6-2T
Function	2x Delay ON
Supply terminals	A1-A2
Voltage range	AC/DC 24-240V(50-60Hz)
Burden	AC 0.7-3VA/DC 0.5-1.7W
Voltage range	AC 230V(50-60Hz)
Power input	AC max.6VA/1.9W
Supply voltage tolerance	-15%;+10%
Supply indication	green LED
Time ranges	0.1s-10days,ON,OFF
Time setting	potentionmeter
Time deviation	10%-mechanical setting
Repeat accuracy	0.2%-set value stability
Temperature coecient	0.05% /°C,at=20°C(0.05°F, at=68°F)
Output	2×SPDT
Current rating	10A/AC1
Switching voltage	250VAC/24VDC
Min.breaking capacity DC	500mW
Output indication	red LED
Mechanical life	1×10 ⁷
Electrical life(AC1)	1×10 ⁵
Reset time	max.200ms
Operating temperature	-20°C to +55°C (-4°F to 131°F)
Storage temperature	-35°C to +75°C (-22°F to 158°F)
Mounting/DIN rail	Din rail EN/IEC 60715
Protection degree	IP40 for front panel/IP20 terminals
Operating position	any
Overvoltage cathegory	III.
Pollution degree	2
Max.cable size(mm ²)	solid wire max.1×2.5or 2×1.5/with sleeve max.1×2.5(AWG 12)
Tightening torque	0.4Nm
Dimensions	90×18×64mm
Weight	S240-67g,A230-70g
Standards	EN 61812-1,IEC60947-5-1


Panel Diagram



Wiring Diagram




Functions Diagram



Setting instructions

	Knob 1: delay gear setting, "s" for second, "m" for minute, "h" for hour, "d" for day, "ON" for relay action (15-18/25-28 closed), "OFF" for relay open (15-18/25-28 open).
	Knob 2: ne adjustment of delay time, 10% ~ 100% adjustable.
Delay time = knob 1 × knob 2. Example 1: it needs to be set for 5 seconds. You can set knob 1 to 10s, knob 2 to 50%, and delay time = 10s × 50% = 5s. Example 2: it needs to be set for 8 minutes. You can set knob 1 to 10m, knob 2 to 80%, and delay time = 10m × 80% = 8m.	

Dimensions(mm)



Disposal of Electrical Waste
All electrical waste should be disposed of in compliance with current WEEE regulations.



Caution
The products must be installed by qualified electricians. All and any electrical connections of the product shall comply with the appropriate safety standards.