产品简介
PRODUCT INTRODUCTION

JQX-15F/T90 Electromagnetic relay series


产品图示 PRODUCT ILLUSTRATION



技术参数 TECHNICAL PARAMETER

Dimension	32.4x27.5x19.5
Electric contact	1C.1H.1D
Electric load	30A、40A
Switching Voltage	277VAC/30VDC
contact	Silver alloy
Coil power	DC 0.93W AC 1.2VA
Coil voltage	DC 3V~110V, AC 6V~240V
Electrical life	$\geq 10^5$
Installation	PCB printing plate
Certification	

安装尺寸图 TECHNICAL PARAMETER



JQX-15F/T91 Electromagnetic relay series


产品图示 PRODUCT ILLUSTRATION



技术参数 TECHNICAL PARAMETER

Dimension	32.4x27.4x28.6
Electric contact	1C.1H.1D
Electric load	30A、40A
Switching Voltage	277VAC/30VDC
contact	Silver alloy
Coil power	DC 0.93W AC 1.2VA
Coil voltage	DC 3V~110V, AC 6V~240V
Electrical life	$\geq 10^5$
Installation	PCB printing plate
Certification	

安装尺寸图 TECHNICAL PARAMETER



JQX-15F/T93 Electromagnetic relay series


产品图示 PRODUCT ILLUSTRATION



技术参数 TECHNICAL PARAMETER

Dimension	32.4x27.4x21
Electric contact	1C.1H.1D
Electric load	30A、40A
Switching Voltage	277VAC/30VDC
contact	Silver alloy
Coil power	DC 0.93W AC 1.2VA
Coil voltage	DC 3V~110V, AC 6V~240V
Electrical life	$\geq 10^5$
Installation	PCB printing plate
Certification	

安装尺寸图 TECHNICAL PARAMETER



PYF11A Base series

产品图示 PRODUCT ILLUSTRATION



技术参数 TECHNICAL PARAMETER

Load current	7A
Load voltage	300V
Medium pressure	2500VAC/S
Applicable relay	JQX-18F-3Z、HH53P、MY3

产品简介
PRODUCT INTRODUCTION

PYF08A1、 PYF08A-E1、 PYF08A2 Base series

产品图示 PRODUCT ILLUSTRATION



技术参数 TECHNICAL PARAMETER

Load current	7A
Load voltage	300V
Medium pressure	2500VAC/S
Applicable relay	JQX-18F-2Z、HH52P、MY2

PYF14A1、 PYF14A-E1 Base series

产品图示 PRODUCT ILLUSTRATION



技术参数 TECHNICAL PARAMETER

Load current	7A
Load voltage	300V
Medium pressure	2500VAC/S
Applicable relay	JQX-18F-4Z、HH54P、MY4

PTF08A Base series

产品图示 PRODUCT ILLUSTRATION



技术参数 TECHNICAL PARAMETER

Load current	12A
Load voltage	300V
Medium pressure	2500VAC/S
Applicable relay	JQX-13F-1Z、JQX-13F-2Z、HH61P、HH62P、LY1、LY2

产品简介
PRODUCT INTRODUCTION
致力于未来
FOCUS ON THE FUTURE



※由于标准和材料的变更，文中所述特征和本资料中的图像仅供参考，一切以实物为准，我公司保留最终解释权。

公司简介
COMPANY PROFILE

浙江格亚电气有限公司是一家引进国内外先进的生产设备和技术，专业从事继电器的研发、生产、销售、服务为一体的综合性企业 座落于中国电器之都 柳市。
为能在日益激烈的全球化市场竞争中实现公司的可持续发展，格亚电器将继续秉承 诚信 、 超越 的经营理念、以高性价比的产品、快速的交货期和优越的售后服务来满足全球客户的需求。



产品简介
PRODUCT INTRODUCTION

JQX-13F/2Z Electromagnetic relay series


产品图示 PRODUCT ILLUSTRATION



技术参数 TECHNICAL PARAMETER

Dimension	27.3x21x35
Electric contact	2C.2H.2D
Electric load	12A
Switching Voltage	240VAC/28VDC
contact	Silver alloy
Coil power	DC 0.9W AC 1.2VA
Coil voltage	DC 6V~220V, AC 6V~380V
Electrical life	$\geq 10^5$
Installation	PCB printing plate , base
Certification	

安装尺寸图 TECHNICAL PARAMETER



产品简介
PRODUCT INTRODUCTION

HH52P Electromagnetic relay series


产品图示 PRODUCT ILLUSTRATION



技术参数 TECHNICAL PARAMETER

Dimension	27.3x21x35
Electric contact	2C.2H.2D
Electric load	6.5A
Switching Voltage	240VAC/28VDC
contact	Silver alloy
Coil power	DC 0.9W AC 1.2VA
Coil voltage	DC 3V~220V, AC 3V~380V
Electrical life	$\geq 10^5$
Installation	PCB printing plate , base
Certification	

安装尺寸图 TECHNICAL PARAMETER



HH53P Electromagnetic relay series


产品图示 PRODUCT ILLUSTRATION



技术参数 TECHNICAL PARAMETER

Dimension	27.3x21x35
Electric contact	3C.3H.3D
Electric load	6.5A
Switching Voltage	240VAC/28VDC
contact	Silver alloy
Coil power	DC 0.9W AC 1.2VA
Coil voltage	DC 3V~220V, AC 3V~380V
Electrical life	$\geq 10^5$
Installation	PCB printing plate , base
Certification	

安装尺寸图 TECHNICAL PARAMETER



HH54P Electromagnetic relay series


产品图示 PRODUCT ILLUSTRATION



技术参数 TECHNICAL PARAMETER

Dimension	27.3x21x35
Electric contact	4C.4H.4D
Electric load	5A
Switching Voltage	240VAC/28VDC
contact	Silver alloy
Coil power	DC 0.9W AC 1.2VA
Coil voltage	DC 3V~220V, AC 3V~380V
Electrical life	$\geq 10^5$
Installation	PCB printing plate , base
Certification	

安装尺寸图 TECHNICAL PARAMETER



JQX-13F/3Z Electromagnetic relay series


产品图示 PRODUCT ILLUSTRATION



技术参数 TECHNICAL PARAMETER

Dimension	27.3x31x35
Electric contact	3C.3H.3D
Electric load	12A
Switching Voltage	240VAC/28VDC
contact	Silver alloy
Coil power	DC 1.5W AC 2.5VA
Coil voltage	DC 6V~220V, AC 6V~380V
Electrical life	$\geq 10^5$
Installation	PCB printing plate , base
Certification	

安装尺寸图 TECHNICAL PARAMETER



产品简介
PRODUCT INTRODUCTION

JQX-38F Electromagnetic relay series


产品图示 PRODUCT ILLUSTRATION



技术参数 TECHNICAL PARAMETER

Dimension	55.5x30x37.5
Electric contact	2C.2H.2D.3C.3H.3D
Electric load	40A、50A
Switching Voltage	240VAC/28VDC
contact	Silver alloy
Coil power	DC 2.5W AC 6VA
Coil voltage	DC 6V~220V, AC 6V~380V
Electrical life	$\geq 10^5$
Installation	Base.Bolt type
Certification	

安装尺寸图 TECHNICAL PARAMETER



JQX-40F Electromagnetic relayseries


产品图示 PRODUCT ILLUSTRATION



技术参数 TECHNICAL PARAMETER

Dimension	60x46x46
Electric contact	1C.1H.1D
Electric load	40A
Switching Voltage	240VAC/28VDC
contact	Silver alloy
Coil power	DC 2.0W AC 8.6VA
Coil voltage	DC 6V~220V, AC 6V~380V
Electrical life	$\geq 10^5$
Installation	Bolt type
Certification	

安装尺寸图 TECHNICAL PARAMETER



JQX-60F Electromagnetic relayseries


产品图示 PRODUCT ILLUSTRATION



技术参数 TECHNICAL PARAMETER

Dimension	60x46x46
Electric contact	1C.1H.1D
Electric load	50A、60A
Switching Voltage	240VAC/28VDC
contact	Silver alloy
Coil power	DC 2.0W AC 8.6VA
Coil voltage	DC 6V~220V, AC 6V~380V
Electrical life	$\geq 10^5$
Installation	Bolt type
Certification	

安装尺寸图 TECHNICAL PARAMETER



JQX-13F/4Z 电磁继电器系列

产品图示 PRODUCT ILLUSTRATION



技术参数 TECHNICAL PARAMETER

Dimension	27.3x41x35
Electric contact	4C.4H.4D
Electric load	12A
Switching Voltage	240VAC/28VDC
contact	Silver alloy
Coil power	DC 1.5W AC 3VA
Coil voltage	DC 6V~220V, AC 6V~380V
Electrical life	$\geq 10^5$
Installation	PCB printing plate , base
Certification	

安装尺寸图 TECHNICAL PARAMETER

