




日期/Date

审核/

Filing Clerk



技术参数:

插芯:

- 插针数: 8+PE
 - 额定电流: 10A
 - 额定电压: ~50V/-120V
 - 额定脉冲电压: 0.8kV
 - 污染等级: 3
 - 依据UL/CSA的额定电压: 50V
 - 额定电压(直流电压): 120V
 - 绝缘阻抗: $>10^{10}\Omega$
 - 材料: 聚碳酸酯
 - 颜色: RAL 7032 (浅灰色)
 - 温度范围: -40°C - $+125^{\circ}\text{C}$
 - 依据UL 94的阻燃等级: V0
 - 可插拔次数: >500
- 插针:
- 接线方式: 冷压连接
 - 材料: 铜合金
 - 表面处理:
 - 镀银
 - 镀金
 - 接触电阻: $\leq 3\text{m}\Omega$
 - 线径范围: $0.14\sim 2.5\text{mm}^2$ (26-14 AWG)
 - 工具:
 - 冷压钳: TL02G
 - 退针器: TL00

Technical specification:

Insters:

- No. of contact: 8+PE
 - Rated current: 10A
 - Rated voltage: ~50V/-120V
 - Rated impulse voltage: 0.8kV
 - Pollution degree: 3
 - Rated voltage acc.to UL/CSA: 50V
 - Rated voltage(direct voltage): 120V
 - Insulation resistance: $>10^{10}\Omega$
 - Material: polycarbonate
 - Colour: RAL 7032(light grey)
 - Temperature range: -40°C - $+125^{\circ}\text{C}$
 - Flammability acc.to UL 94: V0
 - Mating cycles: >500
- Contacts:
- Terminal: crimp terminal
 - Material: copper alloy
 - Surface:
 - Hard-silver plated
 - Hard-gold plated
 - Contact resistance: $\leq 3\text{m}\Omega$
 - Wire gauge: $0.14\sim 2.5\text{mm}^2$ (26-14 AWG)
 - Tools:
 - Crimp contact tool: TL02G
 - Contact removal tool: TL00

						表面处理	—			图号	—
						Finish				Drawing No.	
						材料	—			产品代号	HD-008-FC
						Material				Part Code	
标记	数量	变更描述/Description			签名	日期	比例	版本	重量	数量	产品料号
Mark	Number				Signature	Date	Scale	REV.	Weight	Qty.	Part No.
绘图	BQ LUO	18.10.2010	标准化	—	—	—	1:1	V1.0	8g	—	产品名称
Drawn											Part Name
审核	P RAO	18.10.2010									
Checked											
工艺	—	—	批准	YY LIN	18.10.2010						
Process			Approved								
								All Dimensions in mm Original Size DIN A 4			浙江思美克电气科技有限公司 ZHEJIANG SMICO ELECTRIC TECHNOLOGY CO.,LTD