




REV	E.C.N NO.	CONTENT	CHK	DATE

**Technical characteristics:****Specifications**

DIN EN 60 664-1

DIN EN 61 984

Inserts

1. Number of contacts: 72+PE
2. Rated Current: 10A
3. Rated Voltage: 250V
4. Pollution degree: 3
5. Rated impulse voltage: 4KV
6. Insulation resistance: $\geq 10^{10} \Omega$
7. Material: Polycarbonate
8. Rated voltage acc. to UL/CSA: 600V
9. Limiting temperatures: $-40^{\circ}\text{C} \sim +125^{\circ}\text{C}$
10. Flammability acc. to UL94: V0
11. Mechanical working life (mating cycles): ≥ 500

Contacts

1. Material: Copper alloy
2. Surface: hard-silver plated
3. Contact resistance: $\leq 3\text{m}\Omega$
4. Terminal: Crimp terminal
5. Wire gauge: 0.14-2.5mm² (26-14AWG)
6. Stripping length: 6-8mm
7. Rohs Compliance

Note: Crimp contact pins should order separately

ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTE		
DWG.	LZM	DATE	23.11.23	UNITS	MM	SHEET/OF	1 / 1
CHK.		DATE		SCALE	1 : 1	A4	
APP.		DATE		NAME	ULO-HD05-HDD-072-FC		
 NINGBO ULO ELECTRONICS CO.,LTD. 宁波欧路电子有限公司				DWGNO.			