







4-M3*10



技术参数:

插芯:

- 插针数: 4/4+PE

- 额定电流:

· 电力区: 63A

· 信号区: 16A

- 额定电压:

· 电力区: 690V

· 信号区: 250V

- 额定脉冲电压:

· 电力区: 8kV

· 信号区: 4kV

- 污染等级: 3

- 依据UL/CSA的额定电压: 600V/230V

- 绝缘阻抗: $>10^{10}\Omega$

- 材料: 聚碳酸酯

- 颜色: RAL 7032 (浅灰色)

- 温度范围: -40°C - $+125^{\circ}\text{C}$

- 依据UL 94的阻燃等级: V0

- 可插拔次数: >500

插针:

- 接线方式: 轴向螺栓连接/弹片连接

- 材料: 铜合金

- 表面处理: 镀银

- 接触电阻:

· 强电针: $<0.5\text{m}\Omega$

· 信号针: $<1\text{m}\Omega$

- 线径范围:

· 强电针: 14-22mm²(8-4 AWG)

· 信号针: 0.14-2.5mm²(26-14 AWG)

- 最大电缆直径:

· 强电针: 11mm

- 剥线长度:

· 强电针:

· mm²: 16 22

· mm: 11⁺¹ 12.5⁺¹

· 信号针: 7-9mm

Technical specification:

Inserts:

- No. of contact: 4/4+PE

- Rated current:

· Power area: 63A

· Signal area: 16A

- Rated voltage:

· Power area: 690V

· Signal area: 250V

- Rated impulse voltage:

· Power area: 8kV

· Signal area: 4kV

- Pollution degree: 3

- Rated voltage acc.to UL/CSA: 600V/230V

- Insulation resistance: $>10^{10}\Omega$

- Material: polycarbonate

- Colour: RAL 7032(light grey)

- Temperature range: -40°C - $+125^{\circ}\text{C}$

- Flammability acc.to UL 94: V0

- Mating cycles: >500

Contacts:

- Terminal: axial screw terminal/spring terminal

- Material: copper alloy

- Surface: hard-silver plated

- Contact resistance:

· Power contacts: $<0.5\text{m}\Omega$

· Signal contacts: $<1\text{m}\Omega$

- Wire gauge:

· Power contacts: 14-22mm²(8-4 AWG)

· Signal contacts: 0.14-2.5mm²(26-14 AWG)

- Max. insulation diameter:

· Power contacts: 11mm

- Stripping length:

· Power contacts:

· mm²: 16 22

· mm: 11⁺¹ 12.5⁺¹

· Signal contacts: 7-9mm

			订货号 Order No.
版本 REV	重量 weight	比例 Scale	产品代号 Part Code
V1.0		1:1	SO-HK-004/4.2-M
 浙江思美克电气科技有限公司 ZHEJIANG SMICO ELECTRICAL TECHNOLOGY CO.,LTD			