




技术参数:

插芯:

- 插针数: 2
- 额定电流: 40A
- 额定电压: 1000V
- 额定脉冲电压: 8kV
- 污染等级: 3
- 依据UL的额定电压: 600V
- 绝缘阻抗: $>10^{10}\Omega$
- 材料: 聚碳酸酯
- 颜色: RAL 7032 (浅灰色)
- 温度范围: $-40^{\circ}\text{C} - +125^{\circ}\text{C}$
- 依据UL 94的阻燃等级: V0
- 可插拔次数: >500

插针:

- 接线方式: 轴向螺栓连接
- 材料: 铜合金
- 表面处理: 镀银
- 接触电阻: $\leq 1\text{m}\Omega$
- 线径范围: $2.5-10\text{mm}^2$
- 内六角扳手: SW-2*40
- 剥线长度:
 - mm^2 : 2.5 4 6 10
 - mm: 5^{+1} 5^{+1} 8^{+1} 11^{+1}
- 拧紧力矩:
 - mm^2 : 2.5 4 6 10
 - N·m: 1.5 1.5 2 2


Technical specification:

Inserts:

- No. of contact: 2
- Rated current: 40A
- Rated voltage: 1000V
- Rated impulse voltage: 8kV
- Pollution degree: 3
- Rated voltage acc.to UL: 600V
- Insulation resistance: $>10^{10}\Omega$
- Material: polycarbonate
- Colour: RAL 7032(light grey)
- Temperature range: $-40^{\circ}\text{C} - +125^{\circ}\text{C}$
- Flammability acc.to UL 94: V0
- Mating cycles: >500

Contacts:

- Terminal: axial screw terminal
- Material: copper alloy
- Surface: hard-silver plated
- Contact resistance: $\leq 1\text{m}\Omega$
- Wire gauge: $2.5-10\text{mm}^2$
- Hexagonal driver: SW-2*40
- Stripping length:
 - mm^2 : 2.5 4 6 10
 - mm: 5^{+1} 5^{+1} 8^{+1} 11^{+1}
- Tightening torque:
 - mm^2 : 2.5 4 6 10
 - N·m: 1.5 1.5 2 2

 			订货号 Order No.
版本 REV	重量 weight	比例 Scale	产品代号 Part Code
V1.0	-	1:1	SO-HMK-002-F
 浙江思美克电气科技有限公司 ZHEJIANG SMICO ELECTRICAL TECHNOLOGY CO.,LTD			