

技术参数:

插芯:

- 插针数: 6/6+PE
- 额定电流:
 - 电力区: 40A
 - 信号区: 16A
- 额定电压:
 - 电力区: 690V
 - 信号区: 400V
- 额定脉冲电压:
 - 电力区: 8kV
 - 信号区: 6kV
- 污染等级: 3
- 依据UL/CSA的额定电压: 600V/600V
- 绝缘阻抗: $>10^{10}\Omega$
- 材料: 聚碳酸酯
- 颜色: RAL 7032 (浅灰色)
- 温度范围: $-40^{\circ}\text{C} - +125^{\circ}\text{C}$
- 依据UL 94的阻燃等级: V0
- 可插拔次数: ≥ 500

插针:

- 接线方式: 螺钉连接
- 材料: 铜合金
- 表面处理: 镀银
- 接触电阻:
 - 强电针: $\leq 0.3\text{m}\Omega$
 - 信号针: $\leq 1\text{m}\Omega$
- 线径范围:
 - 强电针: 4-10mm²(12-8 AWG)
 - 信号针: 1-2.5mm²(18-14 AWG)
- 拧紧力矩:
 - 强电针:

mm ² : 1.5	2.5	4	6	10	16
N·m: 1.2	2	3	3	3	3
 - 信号针: 0.5N·m

Technical specification:



Insters:

- No. of contact: 6/6+PE
- Rated current:
 - Power area: 40A
 - Signal area: 16A
- Rated voltage:
 - Power area: 690V
 - Signal area: 400V
- Rated impulse voltage:
 - Power area: 8kV
 - Signal area: 6kV
- Pollution degree: 3
- Rated voltage acc.to UL/CSA: 600V/600V
- Insulation resistance: $>10^{10}\Omega$
- Material: polycarbonate
- Colour: RAL 7032(light grey)
- Temperature range: $-40^{\circ}\text{C} - +125^{\circ}\text{C}$
- Flammability acc.to UL 94: V0
- Mating cycles: ≥ 500

Contacts:

- Terminal: screw terminal
- Material: copper alloy
- Surface: hard-silver plated
- Contact resistance:
 - Power contacts: $\leq 0.3\text{m}\Omega$
 - Signal contacts: $\leq 1\text{m}\Omega$
- Wire gauge:
 - Power contacts: 4-10mm²(12-8 AWG)
 - Signal contacts: 1-2.5mm²(18-14 AWG)
- Tightening torque:
 - Power contacts:

mm ² : 1.5	2.5	4	6	10	16
N·m: 1.2	2	3	3	3	3
 - Signal contacts: 0.5N·m

 			订货号 Order No.
版本 REV	重量 weight	比例 Scale	产品代号 Part Code
V1.0		1:1	SO-HWK-006/6-F
 浙江思美克电气科技有限公司 ZHEJIANG SMICO ELECTRICAL TECHNOLOGY CO.,LTD			