




NOTES:

- 1.Rated voltage: 60V
- 2.Rated current: 1A
- 3.withstanding voltage: 800V
- 4.Contact resistance : ≤3mΩ
- 5.levels of protection: IP67
- 6.Salt spray:48h(1m)
- 7.Operating temperature:-25 °C~+85°C
- 8.Mechanical life: ≥100
- 9.RoHS Compliance
- 10.Tolerance:
 - .X ±0.3
 - .XX ±0.1
 - Angles ±1°

ULO-CC01-M5A-XXP-FF-PMXX-SRXXX

Pin:03, 04

SH:Shielded(屏蔽)
无:Unshielded(不屏蔽)

Cable jacket:
A:PVC UL2517
B:PUR UL20549

Cable length
01:1M
...
99: 99M
The line grows business trip:
01~05m:±50mm
06~10m:±100mm
11~30m:±200mm
31~99m:±500mm

3Pin A coding		4Pin A coding	
		4	Black
4	Black	3	Blue
3	Blue	2	White
1	Brown	1	Brown
Conn.1	Wire Color	Conn.1	Wire Color

ITEM	NAME OF PART		NO. OF PART	Q"TY	MATERIAL		NOTE	
DWG.	LZM	DATE	24.1.18	UNITS	MM	SHEET/OF	1/1	
CHK.		DATE		SCALE	1:1	A4		
APP.		DATE						
				NAME	ULO-CC01-M5A-XXP-FF-PMXX-SRXXX			
				DWGNO				