



NOTES:

- 1.Rated voltage: 60V
- 2.Rated current: 1A
- 3.withstanding voltage: 800V
- 4.Contact resistance : ≤3mΩ
- 5.levels of protection: IP67
- 6.Salt spray:48h(1m)
- 7.Operating temperature:-25 °C~+85 °C
- 8.Mechanical life: ≥100
- 9.RoHS Compliance
- 10.Tolerance:  
.X ±0.3  
.XX ±0.1  
Angles ±1°

ULO-CC01-M5A-XXP-MM-PMXX-SLXXX

Pin:03, 04

SH: Shielded(屏蔽)  
无:Unshielded(不屏蔽)

Cable jacket:  
A:PVC UL2517  
B:PUR UL20549

Cable length  
01:1M  
...  
99:99M  
The line grows business trip:  
01~05m:±50mm  
06~10m:±100mm  
11~30m:±200mm  
31~99m:±500mm

| 3Pin A coding |            | 4Pin A coding |            |
|---------------|------------|---------------|------------|
|               |            |               |            |
|               |            | 4             | Black      |
| 4             | Black      | 3             | Blue       |
| 3             | Blue       | 2             | White      |
| 1             | Brown      | 1             | Brown      |
| Conn.1        | Wire Color | Conn.1        | Wire Color |

| ITEM       | NAME OF PART |      | NO. OF PART | Q"TY  | MATERIAL                       |          | NOTE |  |
|------------|--------------|------|-------------|-------|--------------------------------|----------|------|--|
| DWG.       | LZM          | DATE | 24.1.18     | UNITS | MM                             | SHEET/OF | 1/1  |  |
| CHK.       |              | DATE |             | SCALE | 1:1                            | A4       |      |  |
| APP.       |              | DATE |             |       |                                |          |      |  |
|            |              |      |             | NAME  | ULO-CC01-M5A-XXP-MM-PMXX-SLXXX |          |      |  |
| 宁波欧路电子有限公司 |              |      |             | DWGNO |                                |          |      |  |