





NOTES:

- Rated voltage/Rated current:
3/4Pin:60V d.c./3A
5Pin:30V/3A
6/8Pin:30V/1.5A
- Withstanding voltage:
3/4Pin:850V
5/6/8Pin:650V
- Contact resistance : $\leq 3\text{m}\Omega$
- Levels of protection: IP67
- Wire connection mode:soldering
- Operating temperature:-40 °C~+85°C
- RoHS Compliance
- Tolerance:
.X ± 0.3
.XX ± 0.1
Angles $\pm 1^\circ$

3Pin A coding		4Pin A coding		5Pin B coding		6Pin A coding		8Pin A coding	
								8	Red
								7	Blue
						6	Pink	6	Pink
				5	Grey	5	Grey	5	Gray
4	Black	4	Black	4	Black	4	Black	4	Yellow
3	Blue	3	Blue	3	Blue	3	Blue	3	Green
		2	White	2	White	2	White	2	Brown
1	Brown	1	Brown	1	Brown	1	Brown	1	White
Conn.1	Wire Color	Conn.1	Wire Color	Conn.1	Wire Color	Conn.1	Wire Color	Conn.1	Wire Color

ULO-CC02-M8X-XXP-FF-PMXX-SRXXX

Coding:

A:A-Coding

B:B-Coding

Pin: 03, 04,
05, 06, 08

SH:Shielded(屏蔽)

无:Unshielded(不屏蔽)

Cable jacket:

A:PVC UL2517

B:PUR UL20549

Cable length

01:1M

...

99:99M

The line grows business
trip:

01~05m:±50mm

06~10m:±100mm

11~30m:±200mm

31~99m:±500mm

ITEM	NAME OF PART		NO. OF PART	Q"TY	MATERIAL		NOTE	
DWG.	LZM	DATE	24.1.22	UNITS	MM	SHEET/OF	1/1	
CHK.		DATE		SCALE	1:1	A4		
APP.		DATE						
				NAME	ULO-CC02-M8X-XXP-FF-PMXX-SRXXX			
NINGBO ULO ELECTRONICS CO.,LTD. 宁波欧路电子有限公司				DWGNO				