





NOTES:

1.Rated voltage/Rated current:

3/4Pin:60V d.c./3A

5Pin:30V d.c./3A

6/8Pin:30V d.c./1.5A

2.Withstanding voltage:

3/4Pin:850V

5/6/8Pin:650V

3.Contact resistance : $\leq 3\text{m}\Omega$

4.Levels of protection: IP67

5.Wire connection mode:soldering

6.Operating temperature:-40 °C~+85 °C

7.Mechanical life: > 50

8.RoHS Compliance

9.Tolerance:

.X ± 0.3 .XX ± 0.1 Angles $\pm 1^\circ$

ULO-CC02-M8X-XXP-FF-SD-SF001

Coding:

A:A-Coding

B:B-Coding

Pin: 03, 04,
05, 06, 08


001:M10*0.75

002:M8*0.5

003:M8*1.0


004:M12*1.0

005:M8*1.0(plastic)




Panel cut


8Pin A coding




6Pin A coding




5Pin B coding



4Pin A coding



3Pin A coding



ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTE
DWG.	LZM	DATE	24.1.18	UNITS	MM
CHK.		DATE		SCALE	1 : 1
APP.		DATE			
	NAME		ULO-CC02-M8X-XXP-FF-SD-SF001		
	DWGNO				

NINGBO ULO ELECTRONICS CO.,LTD.
宁波欧路电子有限公司