





NOTES:

1.Rated voltage/Rated current:

3/4Pin:60V d.c./3A

5Pin:30V/3A

6/8Pin:30V/1.5A

2.Withstanding voltage:

3/4Pin:850V

5/6/8Pin:650V

3.Contact resistance : $\leq 3\text{m}\Omega$

4.Levels of protection: IP67

5.Operating temperature:-40 °C~+85 °C

6.Mechanical life: ≥ 100

7.RoHS Compliance

8.Tolerance:

.X ± 0.3 .XX ± 0.1 Angles $\pm 1^\circ$

ULO-CC02-M8X-XXP-FF-PXSH-SL001

Coding:

A:A-Coding

B:B-Coding

Pin: 03, 04

05, 06, 08


A:组装式焊接(Solder)

S: 塑胶螺母组装式焊接
(Solder)


B: 组装式锁螺钉 (Screw)

W: 塑胶螺母组装式锁螺
钉 (Screw)


3Pin A coding




4Pin A coding




5Pin B coding



6Pin A coding



8Pin A coding



ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTE
DWG.	LZM	DATE	24.1.23	UNITS	MM
CHK.		DATE		SCALE	1:1
APP.		DATE			
	NINGBO ULO ELECTRONICS CO.,LTD.		NAME	ULO-CC02-M8X-XXP-FF-PXSH-SL001	
	宁波欧路电子有限公司		DWGNO		