

NOTES:

UL Standard

1. Use group	B	C	D
Rated Current	65A	-	-
Rated Voltage	300V	-	-

2. Wire range14-6AWG

IEC Standard

1. Pollution Degree	2
Overvoltage Category	III
Rate Impulse Voltage(kV)	8kV
Rate Voltage(V)	750V
Rate Current(A)	76A

2. Wire range6.0-16mm²

NOTES2:

- 1.Housing: PA66(UL94V-2)
- 2.Current carrier: Steel(Zn Plated)
- 3.Screw: Steel(Zn Plated)

NOTES3:

- 1.Pitch: 14.5mm Poles: 02-12P
- 2.Operating temperature: -40℃~+105℃
- 3.RoHS Compliance

How to order

UL0-TB - PA66H - XXP - Y 0 0 0A

Certificate Factory poles Customer
Series NO. Code requirements

color:
1:Grey 2:Blue 3:Black
4:Green 5:Orange 6:Red
7:transparent 8:Yellow 9:white

ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTE
DWG	LZW	DATE	21.04.21	UNITS	MM
CHK	DATE	SCALE	1:1	SHEET/OF	1/1
APP	DATE	NAME	UL0-TB-PA66H-XXP-Y000A		
NINGBO UL0 ELECTRONICS CO.,LTD.			DWGNO	UL0TBV000A	

Total Pitch Tolerances												Nominal dimension range												—		//	
in mm												in mm												0.2		0.3	
over	over	over	over	over	over	over	over	over	over	over	over	over	over	over	over	over	over	over	over	over	over	over	over	over	over	over	over
0	30	53	70	90	115	150	200	250	0	30	53	70	90	115	150	200	250	0	over	all	0	100	over	0	100	over	
to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	
30	53	70	90	115	150	200	250	320	30	53	70	90	115	150	200	250	320	10	100	100	150	150	150	150	150	150	
±0.18	±0.20	±0.25	±0.3	±0.35	±0.44	±0.55	±0.70	±0.75	±0.20	±0.25	±0.30	±0.35	±0.44	±0.55	±0.70	±0.80	±0.90	0.2	0.3	0.3	0.2	0.3	0.5	0.5	0.5	0.5	