

		2		1	
REV	E.C.N NO.	CONTENT	CHK	DATE	

Technical data:

Product properties

1. Product type: Multi-conductor terminal block
2. Number of connections: 3
3. Number of rows: 1
4. Potentials: 1

Electrical properties

1. Nominal voltage: 1000V
2. Rated surge voltage: 8kV
3. Nominal current: 57A
4. Maximum load current: 70A
5. Nominal cross section: 10mm²
6. Overvoltage category: III
7. Degree of pollution: 3
8. Operating temperature range: -60℃~+110℃

Connection data

1. Conductor cross section rigid: $0,5\text{mm}^2$ – 16mm^2
2. Cross section AWG: 20–6
3. Conductor cross section flexible: $0,5\text{mm}^2$ – 16mm^2
4. Conductor cross section, flexible AWG: 20–6
5. Stripping length: 18mm – 20mm

--	--	--	--	--	--

2	ULO-TB186-PT 10-TWIN BU	Blue
---	-------------------------	------

1	ULO-TB186-PT 10-TWIN	Gray
---	----------------------	------

ITEM	NAME OF PART	Color	Nominal dimension range in mm	
			+	- //
Total Pitch Tolerances in mm				

[illegible]

ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTE
DWG.	SWL	DATE	UNITS	MM	SHEET/OF 1/1
CHK.		DATE	SCALE	1:1	A4
APP.		DATE			
NINGBO ULO ELECTRONICS CO.,LTD.			NAME		
宁波欧路电子有限公司			ULO-IB186-PT10-TWIN-XX		
			DWGNO.		