

规格承认书

SPECIFICATION FOR APPROVAL

JS-N-8-PYF14A001

SPECIFICATION FOR APPROVAL

1 产品类型 (TYPE MODEL)

型号 (TYPE)	PYF14A
特性 (Characteristics)	4Z (4C 转换 changge over)
安装方式 (Installation mode)	导轨安装型 Guide rail mounting type

2 性能 (PERFORMANCE)

2.1 负载 (Load):

插座型号 (Socket type)	PYF14A
负载电流 (Load current)	10A
负载电压 (Insulation voltage)	300V
可应用继电器型号 May be applied for relay type	HH68B-4Z HH68BZ-4Z JQX-18F-4Z HH69B-4Z HH54P MY4

2.2 介质耐电压和绝缘电阻 (DIELECTRIC STRENGTHS AND INSULATION RESISTANCE):

绝缘类型 Insulation type	施加电压部位 Applied voltage position	电压 V Voltage
介质耐压 Dielectric withstand voltage	异极触点间 Heteropolar contact	2000/S
	线圈触点间 Between coil contacts	2000/S
加强绝缘 Reinforced insulation	任一端子与固定导轨 Between every terminal and guide rail	2500/S

2.3 螺纹旋紧扭矩 (Thread tightening torque): 0.8N.m

2.4 连接导线 (Connecting Wire): AWG20-14 (0.5~2.5mm²)

2.5 整体插拔力 (Integral insertion and removal force): 4Z≤120N

2.6 耐腐蚀 (Corrosion resistance): 满足 GB/T2423.17-2008 盐雾试验要求, 试验周期 24h

Meet the requirement of GB/T2423.17-2008 salt spray test, Test period 24h

2.7 使用环境 (Operating environment): -40℃~+85℃

4 标志 (MARKING)


3.1 外壳颜色 (CRUST COLOR): 黑 (Black)

3.2 标志位置 (MARKING POSITION): 侧面 (Beside the body)

3.3 字符颜色 (INK COLOR): 白色 (White)

SPECIFICATION FOR APPROVAL

5: 外形安装接线图 (Outline installation wiring diagram)



⑬ ⑭ : A1 A2
① ② ③ ④ : NC
⑤ ⑥ ⑦ ⑧ : NO
⑨ ⑩ ⑪ ⑫ : COM

