






FILE: 2020-D01VUL0

REV	E.C.N NO.	CONTENT	CHK	DATE



NOTES1:

UL Standard

1. Rating voltage/current: 300V/10A

2. Wire range: 18~24AWG

IEC Standard

1.

Pollution Degree	2
Overvoltage Category	III
Rate Impulse Voltage(KV)	1.25KV
Rate Voltage(V)	130V
Rate Current(A)	10A

2. wire range: 0.5-1.0mm²

3. Torque value: M2, 0.2Nm

NOTES2:

1. Housing(2P): PA66(UL94V-0)

2. Cage: Brass(Sn Plated)

3. Spring: Stainless Steel

4. Screw: Steel(Zn Plated/M2.0)

5. Housing(3P): PA66(UL94V-0)

NOTES3:

1. Pitch: 3.96mm Poles: 02-24P

2. Stripping length: 5mm

3. Operating temperature: -40℃~+105℃

4. RoHS Compliance

How to order

ULO-TB17 - 350/3.96 - XXP - Y 0 0 0A

Certificate
Series NO.Factory
Code

poles

Customer
requirements

color:

1:Grey 2:Blue 3:Black
4:Green 5:Orange 6:Red
7:transparent 8:Yellow 9:White

Total Pitch Tolerances in mm										Nominal dimension range in mm										$\perp$		$\equiv$		$—$		$//$	
over 0	over 30	over 53	over 70	over 90	over 115	over 150	over 200	over 250	over 300	over 0	over 30	over 53	over 70	over 90	over 115	over 150	over 200	over 250	over 300	over 0	over 10	all	over 0	over 100	over 150		
to 30	to 53	to 70	to 90	to 115	to 150	to 200	to 250	to 320	to 30	to 30	to 53	to 70	to 90	to 115	to 150	to 200	to 250	to 320	to 10			to 100	to 150				
±0.18	±0.20	±0.25	±0.3	±0.35	±0.44	±0.55	±0.70	±0.75	±0.20	±0.25	±0.30	±0.35	±0.44	±0.55	±0.70	±0.80	±0.90	0.2	0.3	0.3	0.2	0.3	0.5				

ITEM	NAME OF PART		NO. OF PART	Q"TY	MATERIAL		NOTE	
DWG.	LZW	DATE	21.06.02	UNITS	MM	SHEET/OF	1/1	
CHK.		DATE		SCALE	1:1	A4		
APP.		DATE			ULO-TB17-350/3.96-XXP-Y000A			
 NINGBO ULO ELECTRONICS CO.,LTD. 宁波欧路电子有限公司				NAME				
				DWGNO.	ULOTB17Y000A			



NINGBO ULO ELECTRONICS CO., LTD.

宁波欧路电子有限公司