



FILE: 2021-D01VUL0									
REV		EC.N NO.		CONTENT		CHK		DATE	




NOTES1:
UL Standard
1.Rating voltage/current: 300V/10A
2.Wire range: 26-16AWG
IEC Standard
1.Rating voltage/current: 320V/17.5A
3.wire range: 0.2-15mm²



NOTES2:
1.Housing: PA66(UL 94V-0)
2.Cover: PA66(UL 94V-0)
3.Button: PA66(UL 94V-0)
4.Housing cover: P-A66(UL 94V-0)
5.Conductor: Copper(Sn Plated)
6.Spring: Stainless Steel

NOTES3:
1.Pitch: 5.0mm Poles: 02-24P
2.Stripping length: 9-10mm
3.withstanding voltage: AC2000V/1Min
4.Operating temperature: -40℃~+105℃
5.RoHS Compliance

How to order
UL0-TB26 - 550C/5.0 - XXP - Y 0 0 0A
Certificate Factory poles
Series NO. Code Customer requirements



PCB LAYOUT

Total Pitch Tolerances		Nominal dimension range							
in mm		in mm							
over	over	over	over	over	over	over	over	over	over
0	30	53	70	90	115	150	200	250	0
to	to	to	to	to	to	to	to	to	to
30	53	70	90	115	150	200	250	320	0
to	to	to	to	to	to	to	to	to	to
53	70	90	115	150	200	250	320	30	53
to	to	to	to	to	to	to	to	to	to
±0.18	±0.20	±0.25	±0.3	±0.35	±0.44	±0.55	±0.70	±0.75	±0.20
±0.35	±0.44	±0.55	±0.70	±0.75	±0.20	±0.25	±0.30	±0.35	±0.44
±0.55	±0.70	±0.80	±0.90	0.2	0.3	0.3	0.3	0.2	0.3
0.5									

ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTE
DWG.	LZW	DATE	21.12.15	UNITS	MM
CHK.	DATE	SCALE	1:1	SHEET/OF	A4
APP.	DATE	NAME	UL0-TB26-550C/5.0-XXP-Y000A		

