

		2		1	
REV	E.C.N NO.	CONTENT	CHK	DATE	

NOTES:

UL Standard

1

Use group	B	C	D
Rated Current	10A	10A	10A
Rated Voltage	300V	150V	300V

2.Wire range:28-16AWG

IEC Standard

1

Pollution Degree	2
Overvoltage Category	III
Rate Impulse Voltage(KV)	4.0KV
Rate Voltage(V)	320V
Rate Current(A)	20A

2. Wire range: 0.2-2.5mm²

NOTES:

1.Housing: PA66(UL94V-0)

2.Cover:PA66(UL94V-0)

3. Cage: Brass (Ni Plated)

4. Clamp: Phosphor Brons (Ni Plated)

5.Screw:Steel(Zn Plated)

6. Block: Steel(Zn Plated)

7.Screw:Steel(Zn Plated/M2.5)

NOTES:

1.Pitch: 5.08mm Poles: 02-24P

2.Stripping length: 10mm

3. Operating temperature: $-40^{\circ}\text{C} \sim +105^{\circ}\text{C}$

4. RoHS Compliance

How to order

UL0-TB28 - 2KCM/5.08 - XXP - Y 0 0 0 A

color:

E OF PART	NO. OF PART	Q'TY	MATERIAL	NOTE
-----------	-------------	------	----------	------

Zw	DATE	21.04.29	UNITS	MM	SHEET/OF	1/1
	DATE		SCALE	1:1	A4	
	DATE					



NINGBO UL0 ELECTRONICS CO.,LTD
宁波欧路电子有限公司

DWGNO.	ULOTB28Y000A
--------	--------------

[illegible]