

		2		1	
REV	E.C.N NO.	CONTENT	CHK	DATE	

NOTES:

UL Standard

1

Use group	B	C	D
Rated Current	10A	10A	10A
Rated Voltage	300V	150V	300V

2. Wire range: 28-12AWG

IEC Standard

1

Pollution Degree	2
Overvoltage Category	III
Rate Impulse Voltage(KV)	4.0KV
Rate Voltage(V)	400V
Rate Current(A)	20A

2. Wire range: 0.2-2.5mm²

NOTES:

- 1.Housing: PA66(UL94V-0)
- 2.Cover:PA66(UL94V-0)
- 3.(Cage:Brass(Ni Plated)
- 4.(Clamp:Phosphor Brons(Ni Plated)
- 5.Screw:Steel(Zn Plated/M3.0)
- 6.Screw:Steel(Zn Plated/M2.5)
- 7.Block: Steel(Zn Plated)

NOTES:

- 1.Pitch: 7.5mm Poles: 02-24P
2.Stripping length: 10mm
3.Operating temperature: -40~+105℃
4.RoHS Compliance

How to order

UL0-TB34 - 2KCM/7.5 - XXP - Y 0 0 0A

Certificate Series NO.	Factory Code	Customer requirements
---------------------------	-----------------	--------------------------

color:

- 1:Grey 2:Blue 3:Black
4:Green 5:Orange 6:Red
7:transparent 8:Yellow 9:White

ITEM	NAME OF PART	NO. OF PART	Q"TY	MATERIAL	NOTE
------	--------------	-------------	------	----------	------

DWG.	LZ W	DATE	22.02.17	UNITS	MM	SHEET/OF	1/1
CHK.		DATE		SCALE	1:1	A4	
APP.		DATE					



NINGBO ULO ELECTRONICS CO., LTD
宁波欧路电子有限公司

DWGNO.	ULOTB34Y000A
--------	--------------