



Pollution Degree	3	2	2
Over-voltage Category	II	II	I
Rate Impulse Voltage(kV)	4kV	4kV	4kV
Rate Voltage(V)	300V	300V	600V
Rate Current(A)	17.5A	17.5A	17.5A

1.

3.Pin header: Copper alloy(M2.5/Sn Plated)

4. RoHS Compliance

JL0-TB38 - 16R/B - XXP - Y 100A

Customer requirements

7
8
9
10
11

5:0range[illegible]

$\pm 0.18 \pm 0.20 \pm 0.25$	± 0.3	± 0.35	$\pm 0.44 \pm 0.55$	± 0.70	± 0.75	± 0.20	± 0.25	± 0.30	± 0.35	± 0.44	± 0.55	± 0.70	± 0.80	± 0.90	0.2	0.3	0.2	0.3	0.5	over
0	30	53	70	90	115	150	200	250	0	30	53	70	90	115	150	200	250	0	100	over
to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to
30	53	70	90	115	150	200	250	320	0	30	53	70	90	115	150	200	250	320	100	150

ITEM	NAME OF PART		NO. OF PART	Q'TY	MATERIAL		NOTE	
DWG.	LZW	DATE	21.05.31	UNITS	MM	SHEET/OF	1/1	
CHK		DATE		SCALE	1 : 1	A4		
APP.		DATE		NAME				
NINGBO ULO ELECTRONICS CO.,LTD				ULO-1B38-16R/B-XXP-Y100A				
				ULOTB38Y100A				
宁波欧路电子有限公司				ULOTB38Y100A				