

NOTES:

UL Standard

Use group	B	C	D
Rated Current	10A	—	—
Rated Voltage	300V	—	—

2. Wire range: 24 ~ 16AWG

IEC Standard

→

Pollution Degree	2
Over-voltage Category	III
Rate Impulse Voltage(KV)	2.5KV
Rate Voltage(V)	250V
Rate Current(A)	10A

2.wire range: 0.2-1.5mm²




NOTES:

1.Pitch: 3.81mm Poles: 02-24P

2.Stripping length:7mm

3. Operating temperature: $-40^{\circ}\text{C} \sim +105^{\circ}\text{C}$

4. RoHS Compliance



Total Pitch Tolerances in mm										Nominal dimension range in mm										—		//	
over	over	over	over	over	over	over	over	over	over	over	over	over	over	over	over	over	over	over	over				
0	30	53	70	90	115	150	200	250	0	30	53	70	90	115	150	200	250	0	over				
to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	all				
30	53	70	90	115	150	200	250	320	30	53	70	90	115	150	200	250	320	10	100				
-0.18		+0.20		+0.25		+0.3		+0.35		+0.44		+0.55		+0.70		+0.75		+0.80					
0.2		0.3		0.3		0.3		0.3		0.3		0.3		0.3		0.3		0.5					

ITEM	NAME OF PART	NO. OF PART	Q-TY	MATERIAL	NOTE
DMG.	/	DATE	/	UNITS	MM
CHK.		DATE		SCALE	1 : 1
APP.		DATE			A4
				NAME	UL0-1B430-8K-3.81-XXP
				DMGNO	X