

		2		1	
REV	E.C.N NO.	CONTENT	CHK	DATE	

NOTES:

UL Standard

—

Use group	B	C	D
Rated Current	20A	—	10A
Rated Voltage	300V	—	300

2. Wire range: 12~22AWG

IEC Standard

1.

Pollution Degree	2
Overvoltage Category	II
Rate Impulse Voltage(KV)	6.0KV
Rate Voltage(V)	320V
Rate Current(A)	24A

2. Wire range: 0.5-2.5mm²

NOTES:

- 1.Housing: PA66(UL94V-0)
- 2.Screw: Steel(M3/Ni Plated)
- 3.Solder Pin: Brass(Tin Plated)

NOTES:

- 1.Pitch: 8.25mm Poles: 02-24P
2.Operating temperature: -40℃~+105℃
3.RoHS Compliance

How to order

UL0-TB43 - 35C/B - XXP - Y 100A

Certificate Series NO.	Factory Code	poles	Customer requirements
---------------------------	-----------------	-------	--------------------------

Customer requirements

—color:

- 1:Grey 6:Red
2:Blue 7:transparent
3:Black 8:Yellow
4:Green 9:White
5:Orange

A																						
Total Pitch Tolerances										Nominal dimension range							—		—		—	
in mm										in mm												
over	over	over	over	over	over	over	over	over	over	over	over	over	over	over	over	over	over	over				
0	30	53	70	90	115	150	200	250	0	30	53	70	90	115	150	200	250	0				
to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to				
30	53	70	90	115	150	200	250	320	30	53	70	90	115	150	200	250	320	10				