

NOTES1:

UL Standard

1.

Use group	B	C	D
Rated Current	15A	—	—
Rated Voltage	300V	—	—

2.Wire range: 24~14AWG

IEC Standard

1.

Pollution Degree	3
Overvoltage Category	III
Rate Impulse Voltage(KV)	4KV
Rate Voltage(V)	250V
Rate Current(A)	16A

2.wire range: 0.2-2.5mm²







NOTES2:

1.Pitch:5.0mm Poles: 02-24P

2.Stripping length: 8-9mm

3.Operating temperature: -40℃~+105℃

4.RoHS Compliance



Total Pitch Tolerances in mm												Nominal dimension range in mm												T		≡		—		//	
over	0	30	53	70	90	115	150	200	250	0	30	over	0	30	53	70	90	115	150	200	250	0	over	0	over	0	100	over			
to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	150			
30	53	70	90	115	150	200	250	320	30	53	70	90	115	150	200	250	320	10	all	100	150	100	150	100	150	100	150	150			
±0.18	±0.20	±0.25	±0.3	±0.35	±0.44	±0.55	±0.70	±0.75	±0.20	±0.25	±0.30	±0.35	±0.44	±0.55	±0.70	±0.80	±0.90	0.2	0.3	0.3	0.2	0.3	0.3	0.2	0.3	0.3	0.5	0.5			
6												5												4							

ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL		NOTE
DWG.	/	/	UNITS	MM	SHEET/OF	1 / 1
CHK.	DATE		SCALE	1 : 1	A4	
APP.	DATE		ULO-TB440-8KC-5.0-XXP			
 NINGBO ULO ELECTRONICS CO.,LTD.						
宁波欧路电子有限公司			DWGNO.	X		
			2		1	