



Pollution Degree	2
Overvoltage Category	III
Rate Impulse Voltage(KV)	4.0K
Rate Voltage(V)	250V
Rate Current(A)	18A

2. Wire range: 1.0-2.5mm²

1.Housing(2P): PA66(UL94V-0)

- 1.Housing(2P): PA66(UL94V-0)
- 2.Housing(3P): PA66(UL94V-0)
- 3.Solder Pin: Brass(Tin Plated)
- 4.Block: Brass(Ni Plated)
- 5.Screw: Steel(M2.5,Zn Plated)

1.Pitch: 5.08mm Poles: 02-24F

2.Stripping length: 6mm

3. Operating temperature: $-40^{\circ}\text{C} \sim +105^{\circ}\text{C}$

4. RoHS Compliance

How to order

UL0-TB93	-	500V/5.08	-	XXP	-	Y	0 0 0A
----------	---	-----------	---	-----	---	---	--------

Certificate Series NO.	Factory Code	Customer requirements
---------------------------	-----------------	--------------------------

Customer requirements

1:Grey 6:Red
2:Blue 7:transparent
3:Black 8:Yellow
4:Green 9:White
5:Orange

ITEM	NAME OF PART	NO. OF PART	Q-TY	MATERIAL	NOTE
DWG.	LZW	DATE 21.05.08	UNITS	MM	SHEET/OF 1/1
CHK.		DATE	SCALE	1 : 1	A4
APP.		DATE			
NINGBO UL0 ELECTRONICS CO.,LTD. 宁波欧路电子有限公司			UL0-1B93-500V/5.08-XP- Y000A		
DWGNO.	UL01B93Y0000A				