


Technical data:

Product properties



- Product type: Feed-through terminal block
- Number of connections: 2
- Number of rows: 1
- Potentials: 1

Electrical properties

- Nominal voltage: 800V
- Rated surge voltage: 8KV
- Nominal current: 41A
- Maximum load current: 57A
- Nominal cross section: 6mm²
- Overvoltage category: III
- Degree of pollution: 3
- Operating temperature range: -60℃~+110℃

Connection data

- Conductor cross section rigid: 0.2mm²-10mm²
- Cross section AWG: 24-8
- Conductor cross section flexible: 0.2mm²-6mm²
- Conductor cross section, flexible AWG: 24-10
- Stripping length: 10mm



2	UL0-TB334-UK 6 N BU	Blue
1	UL0-TB334-UK 6 N	Gray

ITEM	NAME OF PART	Color
------	--------------	-------

Total Pitch Tolerances		Nominal dimension range																	
		in mm																	
		0	30	53	70	90	115	150	200	250	320	30	53	70	90	115	150	200	250
		to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to
		30	53	70	90	115	150	200	250	320	30	53	70	90	115	150	200	250	320
		±0.18	±0.20	±0.25	±0.3	±0.35	±0.44	±0.55	±0.70	±0.75	±0.20	±0.25	±0.30	±0.35	±0.44	±0.55	±0.70	±0.80	±0.90
		6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6

ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTE	
DWG.	SWL	DATE	24.1.12	UNITS	MM	SHEET/OF
CHK.		DATE		SCALE	1 : 1	A4
APP.		DATE		NAME	UL0-TB334-UK6N-XX	
				DWGNO.		



NINGBO ULO ELECTRONICS CO.,LTD.

宁波欧路电子有限公司