

FILE: 2106.03		6		5		4		3		2		1	
REV		E.C.N NO.		CONTENT		CHK		DATE					

Technical data:

Product properties




- Product type:Ground terminal block
- Number of connections: 1
- Number of rows: 2
- Potentials: 1

Electrical properties

- Nominal voltage: /
- Rated surge voltage: 8kV
- Nominal current: /
- Maximum load current: /
- Nominal cross section: 2. 5mm²
- Overvoltage category: III
- Degree of pollution: 3
- Operating temperature range: -60℃~+110℃
- Insulating material: PA
- Flammability rating according to UL 94: V0

Connection data

- Conductor cross section rigid: 0. 2mm²~4mm²
- Cross section AWG: 24~12
- Conductor cross section flexible: 0. 2mm²~2. 5mm²
- Conductor cross section, flexible AWG: 24~14
- Stripping length: 8mm



Total Pitch Tolerances in mm										Nominal dimension range in mm										—		//	
over	over	over	over	over	over	over	over	over	over	over	over	over	over	over	over	over	over	over	over	over	over	over	over
0	30	53	70	90	115	150	200	250	300	30	53	70	90	115	150	200	250	300	30	53	70	90	115
to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to
30	53	70	90	115	150	200	250	300	30	53	70	90	115	150	200	250	300	30	53	70	90	115	150
±0.18	±0.20	±0.25	±0.3	±0.35	±0.44	±0.55	±0.70	±0.75	±0.20	±0.25	±0.30	±0.35	±0.44	±0.55	±0.70	±0.80	±0.90	0.2	0.3	0.3	0.2	0.3	0.5
6										5										4		3	

ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTE
DWG.	SWL	DATE	24.1.12	UNITS	MM
CHK.	DATE	SCALE	1:1	SHEET/OF	A4 1/1
APP.	DATE	NAME	UL0-TB140-USLKG 3N		



NINGBO ULO ELECTRONICS CO.,LTD.
宁波欧路电子有限公司

DWGNO. X